



## CARATTERISTICHE

### UPPER

Drummed leather Hydro 1,6-1,8 mm

### LINING

3D Air circulation 320 gr.

### ANTISLIP LINING

DUALMICRO

### INSOLE

Five 4 Fit

### TOE CAP

Alu SXT 2.0 Toe cap

### RESISTANCE TO PERFORATION

Zero(K) Perforation resistant

### TYPE

Low Shoe



## SRC (SRA+SRB)

		SOLE 92	PU - TPU
SRA CERAMIC + DETERGENT SOLUTION	FLAT $\geq 0.32$ HEEL (CONTACT ANGLE 7°) $\geq 0.28$	0.40	0.53
SRB STEEL + GLYCEROL	FLAT $\geq 0.18$ HEEL (CONTACT ANGLE 7°) $\geq 0.13$	0.25	0.15
EN ISO 20344:2011			



EN ISO 20345:2011



RITMO

## DANCE

92195-00L

S3 SRC

Taglie: 35-48

Peso: 510 gr.

Calzata: 11

### Settori di utilizzo:

Finishing-off building, Logistics and Light Industry, Components and Automotive



## TECHNOLOGIES

### Removable Insole



Highly breathable and absorbent anatomic insole. Multilayer structure to take advantage of the peculiarities of each component. Dry and with a comfortable memory foam "pillow"



### Protection elements



A new aluminium multi-thicknesses toecap, which delivers a highly performing protection where needed. Resistant to impact of over 200J. Non Metallic anti-perforation insert. Resistant to over 1100 N with zero perforation.



### Lateral stability



Ergonomic rigid internal structure. It houses the heel into the right seat, adjusting the foot support and control of the ankle sideways movements. It keeps the foot tight to the shoe, allowing the perfect fit.



### Torsional stability



Support made of rigid plastic material. It stabilizes the heel bone, the instep and tarsal joints, without altering energy absorption. A support for the natural movement of the foot; it provides comfort and greater stability.



### Electrical features



Wire Electricity Discharge

Strip with 4 filaments of carbon fiber, ensuring proven anti-static properties of the footwear over time.



### Other



Double non-slip layer of microfibre, resistant up to 200,000 cycles. Makes the footwear more comfortable, blocking the foot during use.