




EN ISO 20345:2011 


RITMO  
**MENEITO BOA®**  
91439-01L

**S1P SRC**

**Size:** 35-48  
**Weight:** 520 gr.

**Fit:** 11

**Working Environment:**  
Finishing-off building, Logistics and Light Industry, Components and Automotive, ESD Areas



**FEATURES**

**UPPER**

MicroFiber Suede 1,6-1,8 mm  
SpiderMesh HT  
Digitex Airy  
MicroFiber Suede with Pro-tech  
SXT light 1,6-1,8 mm

**LINING**

3D Air circulation 320 gr.

**ANTISLIP LINING**

DUALMICRO

**INSOLE**

Five 4 Fit

**TOE CAP**

Alu SXT 2.0 Toe cap

**RESISTANCE TO PERFORATION**

KX Antiperforation PS

**TYPE**

Sandal

**SOLE**

**PU / PU ESD-PLUS SRC**

Double density PU sole, Outer- and in-between sole with ESD compound. For use in contact with sensitive electronic equipment. Light and comfortable, very versatile, highly non-slip SRC Antislip standard.

**TECHNOLOGIES**


**Removable Insole**



Highly breathable and absorbent anatomic insole. Multilayer structure to take advantage of the peculiarities of each component. Dry and with a comfortable memory foam "pillow"



**Protection elements**



Toecap "Alu Sxt 2.0" with differentiated thicknesses, resistant to 200J. Non metal perforation resistant Insert to over 1100 N with a 3.0 mm truncated cone nail. Protection over the entire sole of the foot. Flexible and comfortable



**Lateral stability**



Ergonomic rigid internal structure. It houses the heel into the right seat, adjusting the foot support and control of the ankle sideways movements. It keeps the foot tight to the shoe, allowing the perfect fit.



**Torsional stability**



Support made of rigid plastic material. It stabilizes the heel bone, the instep and tarsal joints, without altering energy absorption. A support for the natural movement of the foot; it provides comfort and greater stability.



**Electrical features**



ESD footwear discharge static electricity and avoid damaging surrounding objects; they are designed in compliance with the following standards: IEC EN 61340-5-1:2016 - IEC EN 61340-4-3:2018 - IEC EN 61340-4-5:2018.

**Other**



A patented closing system with a multi coated stainless steel cable. The BOA® Fit System delivers micro-adjustable precision fit, engineered to perform in the toughest conditions.



**SRC (SRA+SRB)**



SOLE 91  
PU - PU

|  |                                    |      |
|--|------------------------------------|------|
| SRA<br>CERAMIC<br>+<br>DETERGENT<br>SOLUTION | FLAT<br>≥0.32                      | 0.54 |
|  | HEEL<br>(CONTACT ANGLE °)<br>≥0.28 |      |
| SRB<br>STEEL<br>+<br>GLYCEROL                | FLAT<br>≥0.18                      | 0.29 |
|  | HEEL<br>(CONTACT ANGLE °)<br>≥0.13 |      |

EN ISO 20344:2011