sixton SAFETY SHOES peak

EN ISO 20345:2011

RITMO

MENEITO

91355-01

S1 SRC

Size: 35-48
Weight: 500 gr.

Fit: 11

Working Environment:
Finishing-off building, Logistics and Light Industry, Components and Automotive, ESD Areas

FEATURES

UPPER
MicroFiber Suede 1,6-1,8 mm
Digitex Airy
MicroFiber Suede with Pro-tech
SXT light 1,6-1,8 mm

LINING
3D Air circulation 320 gr.

ANTISLIP LINING
DUALMICRO

INSOLE
Five 4 Fit

TOE CAP
Alu SXT 2.0 Toe cap

TYPE
Sandal

SOLE
PU / PU ESD-PLUS SRC
Double density PU sole, Outer- and in-between sole with ESD compound. For use in contact with sensitive electronic equipment. Light and comfortable, very versatile, highly non-slip SRC Antislip standard.

SRC (SRA+SRB)

SOLE 91
PU - PU

SRA CERAMIC + DETERGENT SOLUTION	FLAT ≥0.32	0.54
	HEEL (CONTACT ANGLE 7°) ≥0.28	0.52
SRB STEEL + GLYCEROL	FLAT ≥0.18	0.29
	HEEL (CONTACT ANGLE 7°) ≥0.13	0.23

EN ISO 20344:2011

TECHNOLOGIES

Removable Insole

FIVE4FIT

Highly breathable and absorbent anatomic insole.Multilayer structure to take advantage of the peculiarities of each component. Dry and with a comfortable memory foam "pillow"

Protection elements

alu-sxt 2.0 aluminium

The result of the evolution of the latest aluminium technologies. A new multi-thicknesses toe cap, which delivers a highly performing protection where needed. Ultralight protection, keeping comfortable inner volumest.

Lateral stability

dynamic HC control technology

Ergonomic rigid internal structure. It houses the heel into the right seat, adjusting the foot support and control of the ankle sideways movements. It keeps the foot tight to the shoe, allowing the perfect fit.

Torsional stability

STABIL•ACTIVE

Support made of rigid plastic material. It stabilizes the heel bone, the instep and tarsal joints, without altering energy absorption. A support for the natural movement of the foot; it provides comfort and greater stability.

Electrical features

ESD

ESD footwear discharge static electricity and avoid damaging surrounding objects; they are designed in compliance with the following standards: IEC EN 61340-5-1:2016 - IEC EN 61340-4-3:2018 - IEC EN 61340-4-5:2018.

Other

Strip with 4 filaments of carbon fiber, ensuring proven anti-static properties of the footwear over time.

Maspica Srl a Socio Unico Via Einstein,6 - 35020 Casalserugo - Padova / Italy - Cap. Soc. 1.050.000 i.v. - cod. fisc. e Reg. Imp. 04009100282 p. iva IT04009100282
C.C.I.A.A./R.E.A.354572 tel. +39 049 8740771 fax +39 049 8741376 www.sixton.it - info@maspica.it

Questo documento è di proprietà di Maspica Srl a Socio Unico, che si riserva di modificarne i contenuti. È vietata ogni riproduzione, anche parziale