



EN ISO 20345:2011



RITMO

SAMBA
91180-03L
S1P SRC
Size: 35-48

Weight: 510 gr.

Fit: 11

Working Environment:

 Finishing-off building, Logistics
 and Light Industry, Components
 and Automotive, Multipurpose


FEATURES

UPPER

 Drummed Suede Leather Hydro
 1,6-1,8 mm

LINING

3D Air circulation 320 gr.

ANTISLIP LINING
 DUALMICRO

INSOLE

Five 4 Fit

TOE CAP

Alu SXT 2.0 Toe cap

RESISTANCE TO PERFORATION

KX Antiperforation PS

TYPE

Low Shoe

SOLE

PU DUAL-DENSITY SRC

 Double density PU outsole with
 tread designed mainly for indoor
 use. Self-cleaning design and
 highly non-slip grip. SRC Antislip
 standard.

TECHNOLOGIES

Removable Insole

FIVE 4 FIT

 Highly breathable and absorbent
 anatomic insole. Multilayer structure
 to take advantage of the peculiarities
 of each component. Dry and with a
 comfortable memory foam "pillow"


Protection elements


 RESISTANT
 TO 3.0 mm.
 NAILS

alu-sxt2.0
 aluminium

 Toecap "Alu Sxt 2.0" with
 differentiated thicknesses, resistant
 to 200J. Non metal perforation
 resistant Insert to over 1100 N with a
 3.0 mm truncated cone nail. Protection
 over the entire sole of the foot.
 Flexible and comfortable


Lateral stability

dynamic HC control
 technology

 Ergonomic rigid internal structure. It
 houses the heel into the right seat,
 adjusting the foot support and control
 of the ankle sideways movements. It
 keeps the foot tight to the shoe,
 allowing the perfect fit.


Torsional stability


STABIL • ACTIVE

 Support made of rigid plastic
 material. It stabilizes the heel bone,
 the instep and tarsal joints, without
 altering energy absorption. A support
 for the natural movement of the foot;
 it provides comfort and greater
 stability.


Electrical features

WED

Wire Electricity Discharge

 Strip with 4 filaments of carbon fiber,
 ensuring proven anti-static properties
 of the footwear over time.


Other

DUAL MICRO
DUAL MICRO

 Double non-slip layer of microfibre,
 resistant up to 200,000 cycles. Makes
 the footwear more comfortable,
 blocking the foot during use.


SRC (SRA+SRB)


 SOLE 91
 PU - PU

SRA CERAMIC + DIETERTENT SOLUTION	FLAT ≥0.32 HEEL (CONTACT ANGLE 7°) ≥0.28	0.54
SRB STEEL + GLYCEROL	FLAT ≥0.18 HEEL (CONTACT ANGLE 7°) ≥0.13	0.29
		0.23

EN ISO 20344:2011