



EN ISO 20345:2011

RITMO

TIMBA
91294-01L
S1P SRC
Size: 35-48

Weight: 540 gr.

Fit: 11

Working Environment:

Finishing-off building, Logistics
and Light Industry, Components
and Automotive, Multipurpose


FEATURES

UPPER

Drummed Suede Leather Hydro
1,6-1,8 mm
Mesh H.T. no ladder
3D Air circulation 320 gr.

LINING

3D Air circulation 320 gr.

ANTISLIP LINING DUALMICRO

INSOLE

Five 4 Fit

TOE CAP

Alu SXT 2.0 Toe cap

RESISTANCE TO PERFORATION

KX Antiperforation PS

TYPE

Low Shoe

SOLE

PU / PU ESD-PLUS SRC

Double density PU sole, Outer- and
in-between sole with ESD
compound. For use in contact with
sensitive electronic equipment.
Light and comfortable, very
versatile, highly non-slip SRC
Antislip standard.

TECHNOLOGIES

Removable Insole


Highly breathable and absorbent
anatomic insole. Multilayer structure
to take advantage of the peculiarities
of each component. Dry and with a
comfortable memory foam "pillow"


Protection elements

ZERO(k) ANTIPERFORATION

alu-sxt2.0
aluminium

A new aluminium multi-thicknesses
toecap, which delivers a highly
performing protection where needed.
Resistant to impact of over 200J. Non
Metallic anti-perforation insert.
Resistant to over 1100 N with zero
perforation.


Lateral stability

dynamic **HC** control
technology

Ergonomic rigid internal structure. It
houses the heel into the right seat,
adjusting the foot support and control
of the ankle sideways movements. It
keeps the foot tight to the shoe,
allowing the perfect fit.


Torsional stability

STABIL•ACTIVE

Support made of rigid plastic
material. It stabilizes the heel bone,
the instep and tarsal joints, without
altering energy absorption. A support
for the natural movement of the foot;
it provides comfort and greater
stability.


Electrical features


ESD footwear discharge static
electricity and avoid damaging
surrounding objects; they are
designed in compliance with the
following standards: IEC EN
61340-5-1:2016 - IEC EN
61340-4-3:2018 - IEC EN
61340-4-5:2018.

Other

Strip with 4 filaments of carbon fiber,
ensuring proven anti-static properties
of the footwear over time.


SRC (SRA+SRB)


SOLE 91
PU - PU

SRA CERAMIC + DETERGENT SOLUTION	FLAT ≥0.32	0.54
	HEEL (CONTACT ANGLE 7°) ≥0.28	0.52
SRB STEEL + GLYCEROL	FLAT ≥0.18	0.29
	HEEL (CONTACT ANGLE 7°) ≥0.13	0.23

EN ISO 20344:2011