



FEATURES

UPPER
MicroFiber Suede 1,6-1,8 mm

LINING
3D Air circulation 320 gr.

ANTISLIP LINING
DUALMICRO

INSOLE
Five 4 Fit

TOE CAP
Alu SXT 2.0 Toe cap

RESISTANCE TO PERFORATION
KX Antiperforation PS

TYPE
Low Shoe



PU - PU
SOLE 93

BASIC
CERAMIC WITH
NALS

SR
CERAMIC WITH
GLYCERINE

SLIP RESISTANCE

EN ISO 20345:2022

FORWARD HEELSLIP ≥ 0,31	0,35
BACKWARD FOREPART SLIP ≥ 0,36	0,45
FORWARD HEELSLIP ≥ 0,19	0,22
BACKWARD FOREPART SLIP ≥ 0,22	0,35



EN ISO 20345:2022/A1:2024



RITMO CROSS

DOBLE

93517-03L

S3S FO SR

Size: 35-48

Weight: 540 gr.

Fit: 11

Working Environment:

Multipurpose, Finishing-off building, Logistics and Light Industry, ESD Areas



TECHNOLOGIES

Removable Insole



Highly breathable and absorbent anatomic insole. Multilayer structure to take advantage of the peculiarities of each component. Dry and with a comfortable memory foam "pillow"



Protection elements



Toecap "Alu Sxt 2.0" with differentiated thicknesses, resistant to 200J. Non metal perforation resistant Insert to over 1100 N with a 3.0 mm truncated cone nail. Protection over the entire sole of the foot. Flexible and comfortable



Lateral stability



Ergonomic rigid internal structure. It houses the heel into the right seat, adjusting the foot support and control of the ankle sideways movements. It keeps the foot tight to the shoe, allowing the perfect fit.



Torsional stability



Support made of rigid plastic material. It stabilizes the heel bone, the instep and tarsal joints, without altering energy absorption. A support for the natural movement of the foot; it provides comfort and greater stability.



Electrical features



ESD footwear discharge static electricity and avoid damaging surrounding objects; they are designed in compliance with the following standards: IEC EN 61340-5-1:2016 - IEC EN 61340-4-3:2018 - IEC EN 61340-4-5:2018.

Other



Double non-slip layer of microfibre, resistant up to 200,000 cycles. Makes the footwear more comfortable, blocking the foot during use.