



EN ISO 20344:2011



RITMO CROSS
SOUND
93339-00L

S3 SRC

Size: 35-48
Weight: 640 gr.

Fit: 11

Working Environment:
Building, Finishing-off building,
Farming and Gardening, ESD
Areas



FEATURES

UPPER

Greased Nubuk Leather Hydro
Pu Coated Leather 1,6-1,8 mm
No ladder H.T. Fabric

LINING

3D Air circulation 320 gr.

ANTISLIP LINING

DUALMICRO

INSOLE

Five 4 Fit

TOE CAP

Alu SXT 2.0 Toe cap

RESISTANCE TO PERFORATION

KX Antiperforation PS

TYPE

Ankle boot

SOLE

PU / PU ESD-PLUS SRC

Double density PU sole, Outer- and in-between sole with ESD compound. For use in contact with sensitive electronic equipment. Light and comfortable, very versatile, highly non-slip SRC Antislip standard.


TECHNOLOGIES

Removable Insole



Highly breathable and absorbent anatomic insole. Multilayer structure to take advantage of the peculiarities of each component. Dry and with a comfortable memory foam "pillow"

Protection elements



Toecap "Alu Sxt 2.0" with differentiated thicknesses, resistant to 200J. Non metal perforation resistant Insert to over 1100 N with a 3.0 mm truncated cone nail. Protection over the entire sole of the foot. Flexible and comfortable



Lateral stability



Ergonomic rigid internal structure. It houses the heel into the right seat, adjusting the foot support and control of the ankle sideways movements. It keeps the foot tight to the shoe, allowing the perfect fit.

Torsional stability



Support made of rigid plastic material. It stabilizes the heel bone, the instep and tarsal joints, without altering energy absorption. A support for the natural movement of the foot; it provides comfort and greater stability.



Electrical features



ESD footwear discharge static electricity and avoid damaging surrounding objects; they are designed in compliance with the following standards: IEC EN 61340-5-1:2016 - IEC EN 61340-4-3:2018 - IEC EN 61340-4-5:2018.

Other



Double non-slip layer of microfibre, resistant up to 200,000 cycles. Makes the footwear more comfortable, blocking the foot during use.



SRC (SRA+SRB)



SRA CERAMIC + DETERGENT SOLUTION		SOLE 93 PU - PU
FLAT ≥ 0.32	HEEL (CONTACT ANGLE °) ≥ 0.28	0.40
FLAT ≥ 0.18	HEEL (CONTACT ANGLE °) ≥ 0.13	0.23
SRB STEEL + GLYCEROL		0.21

EN ISO 20344:2011