



EN ISO 20345:2011



RITMO CROSS

**SOUND**
**93339-00L**
**S3 SRC**
**Size:** 35-48

**Weight:** 640 gr.

**Fit:** 11

**Working Environment:**

Building, Finishing-off building,  
Farming and Gardening, ESD  
Areas


## FEATURES

### TOMAIA

Greased Nubuk Leather Hydro  
Pu Coated Leather 1,6-1,8 mm  
No ladder H.T. Fabric

### FODERA

3D Air circulation 320 gr.

### FOD. ANTISCIVOLO

DUALMICRO

### SUOLETTA

Five 4 Fit

### PUNTALE

Alu SXT 2.0 Toe cap

### RESISTENZA ALLA PERFORAZIONE

KX Antiperforation PS

### TIPOLOGIA

Ankle boot

### SUOLA

**PU / PU ESD-PLUS SRC**

Double density PU sole, Outer- and in-between sole with ESD compound. For use in contact with sensitive electronic equipment. Light and comfortable, very versatile, highly non-slip SRC Antislip standard.

## TECNOLOGIE

### Suoletta Intercambiabile



Highly breathable and absorbent anatomic insole. Multilayer structure to take advantage of the peculiarities of each component. Dry and with a comfortable memory foam "pillow"

### Protection elements


**RESISTANT TO 3.0 mm. NAILS**
**alu-sxt2.0**  
aluminium

Toecap "Alu Sxt 2.0" with differentiated thicknesses, resistant to 200J. Non metal perforation resistant Insert to over 1100 N with a 3.0 mm truncated cone nail. Protection over the entire sole of the foot. Flexible and comfortable



### Lateral stability

dynamic **HC** control  
technology

Ergonomic rigid internal structure. It houses the heel into the right seat, adjusting the foot support and control of the ankle sideways movements. It keeps the foot tight to the shoe, allowing the perfect fit.

### Torsional stability


**STABIL • ACTIVE**

Support made of rigid plastic material. It stabilizes the heel bone, the instep and tarsal joints, without altering energy absorption. A support for the natural movement of the foot; it provides comfort and greater stability.



### Electrical features



ESD footwear discharge static electricity and avoid damaging surrounding objects; they are designed in compliance with the following standards: IEC EN 61340-5-1:2016 - IEC EN 61340-4-3:2018 - IEC EN 61340-4-5:2018.

### Other



Double non-slip layer of microfibre, resistant up to 200,000 cycles. Makes the footwear more comfortable, blocking the foot during use.



## SRC (SRA+SRB)


SOLE 93  
PU - PU

SRA CERAMIC + DETERGENT SOLUTION	FLAT ≥0.32	0.40
	HEEL (CONTACT ANGLE 7°) ≥0.28	0.35
SRB STEEL + GLYCEROL	FLAT ≥0.18	0.23
	HEEL (CONTACT ANGLE 7°) ≥0.13	0.21

EN ISO 20344:2011