



EN ISO 20345:2011



SCOUT

**LAVAREDO**
**30407-01L**
**S3 HRO HI WR CI SRC**
**Size:** 36-50  
**Weight:** 830 gr.

**Fit:** 11

**Working Environment:**

Building, Mountains, Farming and Gardening, Wood-metal carpentry



## FEATURES

### UPPER

MicroFiber Suede 1,8-2,0 mm  
 No ladder H.T. Fabric  
 MicroFiber TOP 1,8-2,0 mm  
 Soft Full Grain Leather Hydro Reflex insert  
 No ladder H.T. Fabric

### LINING

3D Air circulation 320 gr.  
 PrimaLoft® insulation for footwear, made with up to 100% post-consumer recycled content, is specifically designed for the rigors of repeated wear and extreme conditions, providing protection from cold and wet weather under compression

### ANTISLIP LINING

DUALMICRO

### INSOLE

Dual insulation

### TOE CAP

Alu SXT 2.0 Toe cap

### RESISTANCE TO PERFORATION

KX Antiperforation PS

### TYPE

Ankle boot

### SOLE

#### PU-RUBBER VIBRAM-FIRE&ICE

PU foam insole, light and comfortable. Modular overtow to protect uppers. VIBRAM rubber tread with Fire & ICE mix for high performance in all temperatures. Self-cleaning design with special SRC grip.

## TECHNOLOGIES

### Removable Insole



Insole perfect for winter use and for footwear with protection against cold "CI". It consists of a highly resistant and absorbing felt piece that keeps the foot dry and warm and of an aluminised film to isolate the foot from the ground.



### Protection elements



Toecap "Alu Sxt 2.0" with differentiated thicknesses, resistant to 200J. Non metal perforation resistant Insert to over 1100 N with a 3.0 mm truncated cone nail. Protection over the entire sole of the foot. Flexible and comfortable



### Lateral stability

**dynamic HC control**  
 technology

Ergonomic rigid internal structure. It houses the heel into the right seat, adjusting the foot support and control of the ankle sideways movements. It keeps the foot tight to the shoe, allowing the perfect fit.



### Torsional stability

**STABIL•ACTIVE**

Support made of rigid plastic material. It stabilizes the heel bone, the instep and tarsal joints, without altering energy absorption. A support for the natural movement of the foot; it provides comfort and greater stability.




### Electrical features



Wire Electricity Discharge


Strip with 4 filaments of carbon fiber, ensuring proven anti-static properties of the footwear over time.



### Other



PrimaLoft® insulation for footwear, made with up to 100% post-consumer recycled content, is specifically designed for the rigors of repeated wear and extreme conditions, providing protection from cold and wet weather under compression



## SRC (SRA+SRB)

	SOLE 30	PU - RUBBER
SRA CERAMIC + DETERGENT SOLUTION	FLAT ≥0.32 HEEL (CONTACT ANGLE °°) ≥0.28	0.53 0.49
SRB STEEL + GLYCEROL	FLAT ≥0.18 HEEL (CONTACT ANGLE °°) ≥0.13	0.23 0.18

EN ISO 20344:2011