



EN ISO 20345:2022



SCOUT

LAVAREDO
30407-01L
S7S FO HI CI SC HRO SR
Size: 36-50

Weight: 830 gr.

Fit: 11

Working Environment:

Building, Mountains, Farming and Gardening, Wood-metal carpentry



FEATURES

UPPER

MicroFiber Suede 1,8-2,0 mm
 No ladder H.T. Fabric
 MicroFiber TOP 1,8-2,0 mm
 Soft Full Grain Leather Hydro Reflex insert
 No ladder H.T. Fabric

LINING

3D Air circulation 320 gr.
 PrimaLoft® insulation for footwear, made with up to 100% post-consumer recycled content, is specifically designed for the rigors of repeated wear and extreme conditions, providing protection from cold and wet weather under compression

ANTISLIP LINING

DUALMICRO

INSOLE

Dual insulation

TOE CAP

Alu SXT 2.0 Toe cap

RESISTANCE TO PERFORATION

KX Antiperforation PS

TYPE

Ankle boot

SOLE

PU-RUBBER VIBRAM-FIRE&ICE

PU foam insole, light and comfortable. Modular overtow to protect uppers. VIBRAM rubber tread with Fire & ICE mix for high performance in all temperatures. Self-cleaning design with special SRC grip.

TECHNOLOGIES

Removable Insole



Insole perfect for winter use and for footwear with protection against cold "CI". It consists of a highly resistant and absorbing felt piece that keeps the foot dry and warm and of an aluminised film to isolate the foot from the ground.



Protection elements



Toecap "Alu Sxt 2.0" with differentiated thicknesses, resistant to 200J. Non metal perforation resistant Insert to over 1100 N with a 3.0 mm truncated cone nail. Protection over the entire sole of the foot. Flexible and comfortable



Lateral stability

dynamic **HC** control
 technology

Ergonomic rigid internal structure. It houses the heel into the right seat, adjusting the foot support and control of the ankle sideways movements. It keeps the foot tight to the shoe, allowing the perfect fit.



Torsional stability

STABIL•ACTIVE

Support made of rigid plastic material. It stabilizes the heel bone, the instep and tarsal joints, without altering energy absorption. A support for the natural movement of the foot; it provides comfort and greater stability.



Electrical features



Wire Electricity Discharge


Strip with 4 filaments of carbon fiber, ensuring proven anti-static properties of the footwear over time.



Other



PrimaLoft® insulation for footwear, made with up to 100% post-consumer recycled content, is specifically designed for the rigors of repeated wear and extreme conditions, providing protection from cold and wet weather under compression



PU - RUBBER

SOLE 30

SLIP RESISTANCE

EN ISO 20344:2021

BASIC CERAMIC WITH NALS

FORWARD HEEL SLIP ≥ 0.31	0,32
BACKWARD FOREPART SLIP ≥ 0.36	0,42

SR CERAMIC WITH GLYCERINE

FORWARD HEEL SLIP ≥ 0.19	0,19
BACKWARD FOREPART SLIP ≥ 0.22	0,22