



EN ISO 20345:2011



SCOUT

LAVAREDO ZIP
30463-00L
S3 HRO HI WR CI SRC
Size: 36-50
Weight: 830 gr.

Fit: 11

Working Environment:

 Building, Farming and Gardening,
 Mountains, Wood-metal
 carpentry


FEATURES

UPPER

MicroFiber Suede 1,8-2,0 mm
 No ladder H.T. Fabric
 MicroFiber TOP 1,8-2,0 mm
 Soft Full Grain Leather Hydro
 Reflex insert
 No ladder H.T. Fabric

LINING

PrimaLoft® insulation for
 footwear, made with up to 100%
 post-consumer recycled content,
 is specifically designed for the
 rigors of repeated wear and
 extreme conditions, providing
 protection from cold and wet
 weather under compression

ANTISLIP LINING

DUALMICRO

INSOLE

Dual insulation

TOE CAP

Alu SXT 2.0 Toe cap

RESISTANCE TO PERFORATION

KX Antiperforation PS

TYPE

Half-knee Boot

SOLE

PU-RUBBER VIBRAM-FIRE&ICE

PU foam insole, light and
 comfortable. Modular overtoe to
 protect uppers. VIBRAM rubber
 tread with Fire & ICE mix for high
 performance in all temperatures.
 Self-cleaning design with special
 SRC grip.

TECHNOLOGIES

Removable Insole



Insole perfect for winter use and for
 footwear with protection against cold
 "CI". It consists of a highly resistant
 and absorbing felt piece that keeps
 the foot dry and warm and of an
 aluminised film to isolate the foot
 from the ground.



Protection elements



RESISTANT
 TO 3.0 mm.
 NAILS



Toecap "Alu Sxt 2.0" with
 differentiated thicknesses, resistant
 to 200J. Non metal perforation
 resistant Insert to over 1100 N with a
 3.0 mm truncated cone nail. Protection
 over the entire sole of the foot.
 Flexible and comfortable



Lateral stability

dynamicHC control
 technology

Ergonomic rigid internal structure. It
 houses the heel into the right seat,
 adjusting the foot support and control
 of the ankle sideways movements. It
 keeps the foot tight to the shoe,
 allowing the perfect fit.



Torsional stability



STABIL•ACTIVE

Support made of rigid plastic
 material. It stabilizes the heel bone,
 the instep and tarsal joints, without
 altering energy absorption. A support
 for the natural movement of the foot;
 it provides comfort and greater
 stability.




Electrical features



Wire Electricity Discharge


Strip with 4 filaments of carbon fiber,
 ensuring proven anti-static properties
 of the footwear over time.



Other



PrimaLoft® insulation for footwear,
 made with up to 100% post-consumer
 recycled content, is specifically
 designed for the rigors of repeated
 wear and extreme conditions,
 providing protection from cold and
 wet weather under compression



SRC (SRA+SRB)



SOLE 30
 PU - RUBBER

SRA CERAMIC + DETERGENT SOLUTION	FLAT ≥0.32	0.53
	HEEL (CONTACT ANGLE °°) ≥0.28	0.49
SRB STEEL + GLYCEROL	FLAT ≥0.18	0.23
	HEEL (CONTACT ANGLE °°) ≥0.13	0.18

EN ISO 20344:2011