



EN ISO 20345:2011


 SCOUT
ORTISEI
 30334-09L

S3 *CI HRO HI WR SRC
Size: 36-50
Weight: 780 gr.

Fit: 11

Working Environment:
 Building, Mountains, Wood-metal
 carpentry, Multipurpose


CARATTERISTICHE

TOMAIA

 MicroFiber Suede 1,8-2,0 mm
 No ladder H.T. Fabric
 MicroFiber TOP 1,8-2,0 mm
 Reflex insert

FODERA

3D Air circulation 320 gr.

FOD. ANTISCIVOLO
 DUALMICRO

SUOLETTA
 Qrs01

PUNTALE

Alu SXT 2.0 Toe cap

RESISTENZA ALLA
PERFORAZIONE

KX Antiperforation PS

TIPOLOGIA

Ankle boot

SUOLA

PU-RUBBER VIBRAM-FIRE&ICE

 PU foam insole, light and
 comfortable. Modular overtow to
 protect uppers. VIBRAM rubber
 tread with Fire & ICE mix for high
 performance in all temperatures.
 Self-cleaning design with special
 SRC grip.

TECNOLOGIE

Suoletta Intercambiabile


 Anatomical breathable insole.
 Resistant fabric with recycled open-
 cell foam that absorbs shocks and
 reduces fatigue. Eliminates sweat
 with its high ability to evaporate it.
 Continuous comfort for months and
 months of use


Elementi di Protezione


 RESISTANT
 TO 3.0 mm.
 NAILS

 Toecap "Alu Sxt 2.0" with
 differentiated thicknesses, resistant
 to 200J. Non metal perforation
 resistant Insert to over 1100 N with a
 3.0 mm truncated cone nail. Protection
 over the entire sole of the foot.
 Flexible and comfortable


Stabilità Trasversale

 dynamic **HC** control
 technology

 Ergonomic rigid internal structure. It
 houses the heel into the right seat,
 adjusting the foot support and control
 of the ankle sideways movements. It
 keeps the foot tight to the shoe,
 allowing the perfect fit.


Stabilità Torsione

STABIL•ACTIVE

 Support made of rigid plastic
 material. It stabilizes the heel bone,
 the instep and tarsal joints, without
 altering energy absorption. A support
 for the natural movement of the foot;
 it provides comfort and greater
 stability.


Caratteristiche Elettriche



Wire Electricity Discharge

 Strip with 4 filaments of carbon fiber,
 ensuring proven anti-static properties
 of the footwear over time.


Altro



+WATERPROOF UPPER

 The HDry membrane is hydrophilic
 with high perspiration capacity. It
 guarantees high performance and
 durability, facilitating the
 maintenance of ideal conditions and
 comfort for the user.


SRC (SRA+SRB)


 SOLE 30
 PU - RUBBER

SRA CERAMIC + DETERGENT SOLUTION	FLAT ≥0.32 HEEL (CONTACT ANGLE °°) ≥0.28	0.53 0.49
SRB STEEL + GLYCEROL	FLAT ≥0.18 HEEL (CONTACT ANGLE °°) ≥0.13	0.23 0.18

EN ISO 20344:2011