sixton SAFETY SHOES peak

**EN ISO 20345:2022**

SCOUT

# ORTISEI

**30334-09L**

**S7S FO HI *CI SC HRO SR**

**Size:** 36-50
**Weight:** 780 gr.

**Fit:** 11

**Working Environment:**
Building, Mountains, Wood-metal carpentry, Multipurpose

## FEATURES

**UPPER**
MicroFiber Suede 1,8-2,0 mm
No ladder H.T. Fabric
MicroFiber TOP 1,8-2,0 mm
Reflex insert

**LINING**
3D Air circulation 320 gr.

**ANTISLIP LINING**
DUALMICRO

**INSOLE**
Qrs01

**TOE CAP**
Alu SXT 2.0 Toe cap

**RESISTANCE TO PERFORATION**
KX Antiperforation PS

**TYPE**
Ankle boot

**SOLE**
**PU-RUBBER VIBRAM-FIRE&ICE**
PU foam insole, light and comfortable. Modular overtoe to protect uppers. VIBRAM rubber tread with Fire & ICE mix for high performance in all temperatures. Self-cleaning design with special SRC grip.

S | A | E | FO | WPA | PS (Ø=3 mm) | HI | *CI (AVAILABLE) | WR | SC | HRO | SR

**PU - RUBBER**
SOLE 30

SLIP RESISTANCE
EN ISO 20344:2021

| | | |
|---|---|---|
| **BASIC** CERAMIC WITH NALS | FORWARD HEEL SLIP ≥ 0.31 | 0,32 |
| | BACKWARD FOREPART SLIP ≥ 0.36 | 0,42 |
| **SR** CERAMIC WITH GLYCERINE | FORWARD HEEL SLIP ≥ 0.19 | 0,19 |
| | BACKWARD FOREPART SLIP ≥ 0.22 | 0,22 |

## TECHNOLOGIES

### Removable Insole

QRS01

Anatomical breathable insole. Resistant fabric with recycled open-cell foam that absorbs shocks and reduces fatigue. Eliminates sweat with its high ability to evaporate it. Continuous comfort for months and months of use

### Protection elements

KX RESISTANT TO 3.0 mm. NAILS

alu-sxt 2.0 aluminium

Toecap "Alu Sxt 2.0" with differentiated thicknesses, resistant to 200J. Non metal perforation resistant Insert to over 1100 N with a 3.0 mm truncated cone nail.Protection over the entire sole of the foot. Flexible and comfortable

### Lateral stability

dynamic HC control technology

Ergonomic rigid internal structure. It houses the heel into the right seat, adjusting the foot support and control of the ankle sideways movements. It keeps the foot tight to the shoe, allowing the perfect fit.

### Torsional stability

STABIL•ACTIVE

Support made of rigid plastic material. It stabilizes the heel bone, the instep and tarsal joints, without altering energy absorption. A support for the natural movement of the foot; it provides comfort and greater stability.

### Electrical features

WED
Wire Electricity Discharge

Strip with 4 filaments of carbon fiber, ensuring proven anti-static properties of the footwear over time.

### Other

HDry

The HDry membrane is hydrophilic with high perspiration capacity. It guarantees high performance and durability, facilitating the maintenance of ideal conditions and comfort for the user.

**Maspica Srl a Socio Unico** Via Einstein,6 - 35020 Casalserugo - Padova / Italy - Cap. Soc. 1.050.000 i.v. - cod. fisc. e Reg. Imp. 04009100282 p. iva IT04009100282
C.C.I.A.A./R.E.A.354572 tel. +39 049 8740771 fax +39 049 8741376 www.sixton.it - info@maspica.it

Questo documento è di proprietà di Maspica Srl a Socio Unico, che si riserva di modificarne i contenuti. È vietata ogni riproduzione, anche parziale