



EN ISO 20345:2011


 SCOUT  
**TONALE**  
 30329-02L

**S3 \*CI HRO HI SRC**
**Size:** 36-50  
**Weight:** 735 gr.

**Fit:** 11

**Working Environment:**  
 Building, Wood-metal carpentry,  
 Farming and Gardening,  
 Mountains


## FEATURES

### TOMAIA

 Greased Nubuk Dakar Leather  
 Hydro 1,8-2,0 mm  
 Reflex insert

### FODERA

3D Air circulation 320 gr.

### FOD. ANTISCIVOLO

DUALMICRO

### SUOLETTA

Qrs01

### PUNTALE

Alu SXT 2.0 Toe cap

### RESISTENZA ALLA PERFORAZIONE

KX Antiperforation PS

### TIPOLOGIA

Ankle boot

### SUOLA

#### PU-RUBBER VIBRAM-FIRE&ICE

PU foam insole, light and comfortable. Modular overtoe to protect uppers. VIBRAM rubber tread with Fire &amp; ICE mix for high performance in all temperatures. Self-cleaning design with special SRC grip.

## TECNOLOGIE

### Suoletta Intercambiabile



Anatomical breathable insole. Resistant fabric with recycled open-cell foam that absorbs shocks and reduces fatigue. Eliminates sweat with its high ability to evaporate it. Continuous comfort for months and months of use



### Elementi di Protezione


 RESISTANT  
 TO 3.0 mm.  
 NAILS


Toecap "Alu Sxt 2.0" with differentiated thicknesses, resistant to 200J. Non metal perforation resistant Insert to over 1100 N with a 3.0 mm truncated cone nail. Protection over the entire sole of the foot. Flexible and comfortable



### Stabilità Trasversale

 dynamic **HC** control  
 technology

Ergonomic rigid internal structure. It houses the heel into the right seat, adjusting the foot support and control of the ankle sideways movements. It keeps the foot tight to the shoe, allowing the perfect fit.



### Stabilità Torsione

**STABIL•ACTIVE**

Support made of rigid plastic material. It stabilizes the heel bone, the instep and tarsal joints, without altering energy absorption. A support for the natural movement of the foot; it provides comfort and greater stability.



### Caratteristiche Elettriche



Wire Electricity Discharge

Strip with 4 filaments of carbon fiber, ensuring proven anti-static properties of the footwear over time.



### Altro



Double non-slip layer of microfibre, resistant up to 200,000 cycles. Makes the footwear more comfortable, blocking the foot during use.



## SRC (SRA+SRB)



SRA CERAMIC + DETERGENT SOLUTION	FLAT ≥0.32	0.53
	HEEL (CONTACT ANGLE 7°) ≥0.28	0.49
SRB STEEL + GLYCEROL	FLAT ≥0.18	0.23
	HEEL (CONTACT ANGLE 7°) ≥0.13	0.18

EN ISO 20344:2011