




**EN ISO 20345:2011** 


**SKIPPER LADY**  
**BOMA**  
**95401-04L**

**S3 SRC**

**Size:** 35-42 Lady  
**Weight:** 440 gr.

**Fit:** 11

**Working Environment:**  
Logistics and Light Industry,  
Components and Automotive, ESD  
Areas



**FEATURES**

**UPPER**  
MicroFiber Suede 1,6-1,8 mm  
Crack Lamé

**LINING**  
3D Air circulation 320 gr.

**ANTISLIP LINING**  
DUALMICRO

**INSOLE**  
Five 4 Fit "lady"

**TOE CAP**  
Alu SXT 2.0 Toe cap

**RESISTANCE TO PERFORATION**  
KX Antiperforation PS

**TYPE**  
Low Shoe

**SOLE**  
**PU DUAL-DENSITY SRC**  
Double density PU outsole with tread designed mainly for indoor use. Self-cleaning design and highly non-slip grip. SRC Antislip standard.

**TECHNOLOGIES**

**Removable Insole**  
**FIVE 4 FIT LADY**

Highly breathable and absorbent anatomic insole. Multilayer structure to take advantage of the peculiarities of each component. Dry and with a comfortable memory foam "pillow"



**Protection elements**  
**KX** RESISTANT TO 3.0 mm. NAILS **alu-sxt2.0** aluminium

Toecap "Alu Sxt 2.0" with differentiated thicknesses, resistant to 200J. Non metal perforation resistant Insert to over 1100 N with a 3.0 mm truncated cone nail. Protection over the entire sole of the foot. Flexible and comfortable



**Lateral stability**  
**dynamic HC control technology**

Ergonomic rigid internal structure. It houses the heel into the right seat, adjusting the foot support and control of the ankle sideways movements. It keeps the foot tight to the shoe, allowing the perfect fit.



**Torsional stability**  
**STABIL•ACTIVE**

Support made of rigid plastic material. It stabilizes the heel bone, the instep and tarsal joints, without altering energy absorption. A support for the natural movement of the foot; it provides comfort and greater stability.



**Electrical features**  


ESD footwear discharge static electricity and avoid damaging surrounding objects; they are designed in compliance with the following standards: IEC EN 61340-5-1:2016 - IEC EN 61340-4-3:2018 - IEC EN 61340-4-5:2018.

**Other**  
**DUALMICRO DUALMICRO**  
Double non-slip layer of microfibre, resistant up to 200,000 cycles. Makes the footwear more comfortable, blocking the foot during use.



**SRC (SRA+SRB)**



		SOLE 95 PU - PU
<b>SRA</b> CERAMIC + DETERGENT SOLUTION	FLAT ≥0.32	<b>0.38</b>
	HEEL (CONTACT ANGLE 7°) ≥0.28	<b>0.34</b>
<b>SRB</b> STEEL + GLYCEROL	FLAT ≥0.18	<b>0.21</b>
	HEEL (CONTACT ANGLE 7°) ≥0.13	<b>0.24</b>

EN ISO 20344:2011