



EN ISO 20345:2011



SKIPPER LADY

**CIMA**

**95398-03L**

**S1P SRC**

**Size:** 35-42 Lady

**Weight:** 420 gr.

**Fit:** 11

**Working Environment:**

Logistics and Light Industry,  
Components and Automotive,  
Wood-metal carpentry, ESD Areas



## FEATURES

### UPPER

Digitex Airy  
MicroFiber Suede with Pro-tech  
SXT light

### LINING

Breezy 3D, two-layers  
combination

### ANTISLIP LINING

DUALMICRO

### INSOLE

Five 4 Fit "lady"

### TOE CAP

Alu SXT 2.0 Toe cap

### RESISTANCE TO PERFORATION

KX Antiperforation PS

### TYPE

Low Shoe

### SOLE

#### PU DUAL-DENSITY SRC

Double density PU outsole with  
tread designed mainly for indoor  
use. Self-cleaning design and  
highly non-slip grip. SRC Antislip  
standard.

## TECHNOLOGIES

### Removable Insole

**FIVE 4 FIT**  
LADY.

Highly breathable and absorbent  
anatomic insole. Multilayer structure  
to take advantage of the peculiarities  
of each component. Dry and with a  
comfortable memory foam "pillow"



### Protection elements



Toecap "Alu Sxt 2.0" with  
differentiated thicknesses, resistant  
to 200J. Non metal perforation  
resistant Insert to over 1100 N with a  
3.0 mm truncated cone nail. Protection  
over the entire sole of the foot.  
Flexible and comfortable



### Lateral stability

dynamic **HC** control  
technology

Ergonomic rigid internal structure. It  
houses the heel into the right seat,  
adjusting the foot support and control  
of the ankle sideways movements. It  
keeps the foot tight to the shoe,  
allowing the perfect fit.



### Torsional stability

**STABIL•ACTIVE**

Support made of rigid plastic  
material. It stabilizes the heel bone,  
the instep and tarsal joints, without  
altering energy absorption. A support  
for the natural movement of the foot;  
it provides comfort and greater  
stability.



### Electrical features



ESD footwear discharge static  
electricity and avoid damaging  
surrounding objects; they are  
designed in compliance with the  
following standards: IEC EN  
61340-5-1:2016 - IEC EN  
61340-4-3:2018 - IEC EN  
61340-4-5:2018.

### Other

The microfibre/ fabric of the toe cap is  
protected by the application of  
pro-tech SXT polyurethane to increase the  
resistance of the upper over time. This  
shoe is recommended for "light" work  
environments.



## SRC (SRA+SRB)



|  |                                    |      |
|--|------------------------------------|------|
| SRA<br>CERAMIC<br>+<br>DETERGENT<br>SOLUTION | FLAT<br>≥0.32                      | 0.38 |
|  | HEEL<br>(CONTACT ANGLE °)<br>≥0.28 |      |
| SRB<br>STEEL<br>+<br>GLYCEROL                | FLAT<br>≥0.18                      | 0.21 |
|  | HEEL<br>(CONTACT ANGLE °)<br>≥0.13 |      |

EN ISO 20344:2011