


EN ISO 20345:2011

SKIPPER LADY
CIMA
95398-02L
S3 SRC
Size: 35-42 Lady

Weight: 420 gr.

Fit: 11

Working Environment:

 Logistics and Light Industry,
 Components and Automotive, ESD
 Areas


FEATURES

UPPER

 Digitex Hydro Airy
 MicroFiber Suede 1,6-1,8 mm
 Digitex Hydro Airy
 MicroFiber Suede with Pro-tech
 SXT light 1,6-1,8 mm

LINING

 Breezy 3D, two-layers
 combination

ANTISLIP LINING

DUALMICRO

INSOLE

Five 4 Fit "lady"

TOE CAP

Alu SXT 2.0 Toe cap

RESISTANCE TO PERFORATION

KX Antiperforation PS

TYPE

Low Shoe

SOLE

PU DUAL-DENSITY SRC

 Double density PU outsole with
 tread designed mainly for indoor
 use. Self-cleaning design and
 highly non-slip grip. SRC Antislip
 standard.

TECHNOLOGIES

Removable Insole


 Highly breathable and absorbent
 anatomic insole. Multilayer structure
 to take advantage of the peculiarities
 of each component. Dry and with a
 comfortable memory foam "pillow"


Protection elements


 Toecap "Alu Sxt 2.0" with
 differentiated thicknesses, resistant
 to 200J. Non metal perforation
 resistant Insert to over 1100 N with a
 3.0 mm truncated cone nail. Protection
 over the entire sole of the foot.
 Flexible and comfortable


Lateral stability


 Ergonomic rigid internal structure. It
 houses the heel into the right seat,
 adjusting the foot support and control
 of the ankle sideways movements. It
 keeps the foot tight to the shoe,
 allowing the perfect fit.


Torsional stability


 Support made of rigid plastic
 material. It stabilizes the heel bone,
 the instep and tarsal joints, without
 altering energy absorption. A support
 for the natural movement of the foot;
 it provides comfort and greater
 stability.


Electrical features


 ESD footwear discharge static
 electricity and avoid damaging
 surrounding objects; they are
 designed in compliance with the
 following standards: IEC EN
 61340-5-1:2016 - IEC EN
 61340-4-3:2018 - IEC EN
 61340-4-5:2018.

Other


 Double non-slip layer of microfibre,
 resistant up to 200,000 cycles. Makes
 the footwear more comfortable,
 blocking the foot during use.


SRC (SRA+SRB)


 SOLE 95
 PU - PU

SRA CERAMIC + DETERGENT SOLUTION	FLAT ≥ 0.32	0.38
	HEEL (CONTACT ANGLE °) ≥ 0.28	
SRB STEEL + GLYCEROL	FLAT ≥ 0.18	0.21
	HEEL (CONTACT ANGLE °) ≥ 0.13	

EN ISO 20344:2011