


**EN ISO 20344:2011**

**SKIPPER LADY**
**MOKA**
**95427-00L**
**S1P SRC**
**Size:** 35-42 Lady

**Weight:** 420 gr.

**Fit:** 11

**Working Environment:**

Multipurpose, Logistics and Light Industry, Components and Automotive



## FEATURES

**TOMAIA**

 Drummed Suede Leather Hydro  
 1,6-1,8 mm  
 Mesh H.T. no ladder  
 MicroFiber Xtop

**FODERA**

3D Air circulation 320 gr.

**FOD. ANTISCIVOLO**

DUALMICRO

**SUOLETTA**

Five 4 Fit "lady"

**PUNTALE**

Alu SXT 2.0 Toe cap

**RESISTENZA ALLA PERFORAZIONE**

Zero(K) Perforation resistant

**TIPOLOGIA**

Low Shoe

**SUOLA**
**PU DUAL-DENSITY SRC**

Double density PU outsole with tread designed mainly for indoor use. Self-cleaning design and highly non-slip grip. SRC Antislip standard.

## TECNOLOGIE

**Suoletta Intercambiabile**


Highly breathable and absorbent anatomic insole. Multilayer structure to take advantage of the peculiarities of each component. Dry and with a comfortable memory foam "pillow"

**Elementi di Protezione**
**ZERO(k)**

ANTIPERFORATION



A new aluminium multi-thicknesses toecap, which delivers a highly performing protection where needed. Resistant to impact of over 200J. Non Metallic anti-perforation insert. Resistant to over 1100 N with zero perforation.


**Stabilità Trasversale**
**dynamic HC control**  
 technology

Ergonomic rigid internal structure. It houses the heel into the right seat, adjusting the foot support and control of the ankle sideways movements. It keeps the foot tight to the shoe, allowing the perfect fit.

**Stabilità Torsione**
**STABIL•ACTIVE**

Support made of rigid plastic material. It stabilizes the heel bone, the instep and tarsal joints, without altering energy absorption. A support for the natural movement of the foot; it provides comfort and greater stability.


**Caratteristiche Elettriche**


Wire Electricity Discharge

Strip with 4 filaments of carbon fiber, ensuring proven anti-static properties of the footwear over time.


**Altro**
**DUALMICRO**  
**DNA TWI BO**

Double non-slip layer of microfibre, resistant up to 200,000 cycles. Makes the footwear more comfortable, blocking the foot during use.


**SRC (SRA+SRB)**

 SOLE 95  
 PU - PU

<b>SRA</b> CERAMIC + DETERGENT SOLUTION	FLAT ≥0.32	<b>0.38</b>
	HEEL (CONTACT ANGLE °) ≥0.28	
<b>SRB</b> STEEL + GLYCEROL	FLAT ≥0.18	<b>0.21</b>
	HEEL (CONTACT ANGLE °) ≥0.13	

EN ISO 20344:2011