



EN ISO 20345:2011


 SKIPPER LADY
WINDEX
95406-03
S1 SRC
Size: 35-42 Lady
Weight: 420 gr.

Fit: 11

Working Environment:
 Logistics and Light Industry,
 Components and Automotive, ESD
 Areas


FEATURES

TOMAIA

MicroFiber Suede 1,6-1,8 mm
 MicroFiber Suede 1,6-1,8 mm
 Cubik Lamé
 Reflex insert

FODERA

Breezy 3D, two-layers
 combination

FOD. ANTISCIVOLO

DUALMICRO

SUOLETTA

Five 4 Fit "lady"

PUNTALE

Alu SXT 2.0 Toe cap

TIPOLOGIA

Low Shoe

SUOLA

PU DUAL-DENSITY SRC

Double density PU outsole with
 tread designed mainly for indoor
 use. Self-cleaning design and
 highly non-slip grip. SRC Antislip
 standard.

TECNOLOGIE

Suoletta Intercambiabile

FIVE 4 FIT
 LADY.

Highly breathable and absorbent
 anatomic insole. Multilayer structure
 to take advantage of the peculiarities
 of each component. Dry and with a
 comfortable memory foam "pillow"



Elementi di Protezione

alu-sxt2.0
 aluminium

The result of the evolution of the
 latest aluminium technologies. A new
 multi-thicknesses toe cap, which
 delivers a highly performing
 protection where needed. Ultralight
 protection, keeping comfortable inner
 volumest.



Stabilità Trasversale

dynamic HC control
 technology

Ergonomic rigid internal structure. It
 houses the heel into the right seat,
 adjusting the foot support and control
 of the ankle sideways movements. It
 keeps the foot tight to the shoe,
 allowing the perfect fit.



Stabilità Torsione

STABIL ACTIVE

Support made of rigid plastic
 material. It stabilizes the heel bone,
 the instep and tarsal joints, without
 altering energy absorption. A support
 for the natural movement of the foot;
 it provides comfort and greater
 stability.



Caratteristiche Elettriche




ESD footwear discharge static
 electricity and avoid damaging
 surrounding objects; they are
 designed in compliance with the
 following standards: IEC EN
 61340-5-1:2016 - IEC EN
 61340-4-3:2018 - IEC EN
 61340-4-5:2018.

Altro

DUALMICRO
DUALMICRO

Double non-slip layer of microfibre,
 resistant up to 200,000 cycles. Makes
 the footwear more comfortable,
 blocking the foot during use.



SRC (SRA+SRB)



SOLE 95
 PU - PU

	FLAT ≥0.32	0.38
SRA CERAMIC + DETERGENT SOLUTION	HEEL (CONTACT ANGLE °) ≥0.28	0.34
SRB STEEL + GLYCEROL	FLAT ≥0.18	0.21
	HEEL (CONTACT ANGLE °) ≥0.13	0.24

EN ISO 20344:2011