



EN ISO 20347:2022



SKIPPER
AUCKLAND
90378-11

O2 FO *CI SR

Size: 38-48
Weight: 495 gr.

Fit: 11

Working Environment:
Components and Automotive,
Multipurpose, Ho.Re.Ca.



FEATURES

UPPER

Digitex Hydro Airy
MicroFiber Suede with Pro-tech
SXT light 1,6-1,8 mm

LINING

Breezy 3D, two-layers
combination

ANTISLIP LINING DUALMICRO

INSOLE

Five 4 Fit

TOE CAP

TYPE

Low Shoe

SOLE

PU / PU ESD-PLUS SRC

Double density PU sole, Outer- and
in-between sole with ESD
compound. For use in contact with
sensitive electronic equipment.
Light and comfortable, very
versatile, highly non-slip SRC
Antislip standard.

TECHNOLOGIES

Removable Insole

FIVE 4 FIT

Highly breathable and absorbent
anatomic insole. Multilayer structure
to take advantage of the peculiarities
of each component. Dry and with a
comfortable memory foam "pillow"



Protection elements

EN ISO 20347:2012

Puncture resistant recycled non-
metallic insert plus 1100N.

Lateral stability

dynamic HC control
technology

Ergonomic rigid internal structure. It
hoses the heel into the right seat,
adjusting the foot support and control
of the ankle sideways movements. It
keeps the foot tight to the shoe,
allowing the perfect fit.



Torsional stability

STABIL•ACTIVE

Support made of rigid plastic
material. It stabilizes the heel bone,
the instep and tarsal joints, without
altering energy absorption. A support
for the natural movement of the foot;
it provides comfort and greater
stability.



Electrical features



ESD footwear discharge static
electricity and avoid damaging
surrounding objects; they are
designed in compliance with the
following standards: IEC EN
61340-5-1:2016 - IEC EN
61340-4-3:2018 - IEC EN
61340-4-5:2018.

Other

DUALMICRO
DUALMICRO

Double non-slip layer of microfibre,
resistant up to 200,000 cycles. Makes
the footwear more comfortable,
blocking the foot during use.

PU - PU SOLE 94

SLIP RESISTANCE EN ISO 20344:2021

BASIC CERAMIC WITH NALS	FORWARD HEEL SLIP ≥ 0.31	0,34	
	BACKWARD FOREPART SLIP ≥ 0.36	0,40	
SR CERAMIC WITH GLYCERINE	FORWARD HEEL SLIP ≥ 0.19	0,29	
	BACKWARD FOREPART SLIP ≥ 0.22	0,40	