



EN ISO 20345:2011



SKIPPER  
**AUCKLAND**  
90378-11

**O2 FO SRC**

**Size:** 38-48  
**Weight:** 495 gr.

**Fit:** 11

**Working Environment:**  
Components and Automotive,  
Multipurpose, Ho.Re.Ca.



## FEATURES

### UPPER

Digitex Hydro Airy  
MicroFiber Suede with Pro-tech  
SXT light 1,6-1,8 mm

### LINING

Breezy 3D, two-layers  
combination

### ANTISLIP LINING DUALMICRO

### INSOLE

Five 4 Fit

### TOE CAP

### TYPE

Low Shoe

### SOLE

#### PU / PU ESD-PLUS SRC

Double density PU sole, Outer- and  
in-between sole with ESD  
compound. For use in contact with  
sensitive electronic equipment.  
Light and comfortable, very  
versatile, highly non-slip SRC  
Antislip standard.

## TECHNOLOGIES

### Removable Insole

#### FIVE 4 FIT

Highly breathable and absorbent  
anatomic insole. Multilayer structure  
to take advantage of the peculiarities  
of each component. Dry and with a  
comfortable memory foam "pillow"



### Protection elements

#### EN ISO 20347:2012

Puncture resistant recycled non-  
metallic insert plus 1100N.

### Lateral stability

#### dynamic HC control technology

Ergonomic rigid internal structure. It  
hoses the heel into the right seat,  
adjusting the foot support and control  
of the ankle sideways movements. It  
keeps the foot tight to the shoe,  
allowing the perfect fit.



### Torsional stability

#### STABIL•ACTIVE

Support made of rigid plastic  
material. It stabilizes the heel bone,  
the instep and tarsal joints, without  
altering energy absorption. A support  
for the natural movement of the foot;  
it provides comfort and greater  
stability.



### Electrical features




ESD footwear discharge static  
electricity and avoid damaging  
surrounding objects; they are  
designed in compliance with the  
following standards: IEC EN  
61340-5-1:2016 - IEC EN  
61340-4-3:2018 - IEC EN  
61340-4-5:2018.

### Other

#### DUALMICRO DUALMICRO

Double non-slip layer of microfibre,  
resistant up to 200,000 cycles. Makes  
the footwear more comfortable,  
blocking the foot during use.



### PU - PU SOLE 94

### SLIP RESISTANCE EN ISO 20344:2021

	FORWARD HEEL SLIP ≥ 0.31	0,34	
<b>BASIC</b> CERAMIC WITH NALS	BACKWARD FOREPART SLIP ≥ 0.36	0,40	
<b>SR</b> CERAMIC WITH GLYCERINE	FORWARD HEEL SLIP ≥ 0.19	0,29	
	BACKWARD FOREPART SLIP ≥ 0.22	0,40	