



EN ISO 20345:2022


 SKIPPER
AUCKLAND
 94378-00L

S3S FO *CI SR
Size: 38-50
Weight: 560 gr.

Fit: 11

Working Environment:
 Logistics and Light Industry,
 Components and Automotive, ESD
 Areas


FEATURES

UPPER

 Digitex Hydro Airy
 MicroFiber Suede with Pro-tech
 SXT light 1,6-1,8 mm

LINING

 Breezy 3D, two-layers
 combination

ANTISLIP LINING DUALMICRO

INSOLE

Five 4 Fit

TOE CAP

Alu SXT 2.0 Toe cap

RESISTANCE TO PERFORATION

KX Antiperforation PS

TYPE

Low Shoe

SOLE

PU / PU ESD-PLUS SRC

 Double density PU sole, Outer- and
 in-between sole with ESD
 compound. For use in contact with
 sensitive electronic equipment.
 Light and comfortable, very
 versatile, highly non-slip SRC
 Antislip standard.

TECHNOLOGIES

Removable Insole


 Highly breathable and absorbent
 anatomic insole. Multilayer structure
 to take advantage of the peculiarities
 of each component. Dry and with a
 comfortable memory foam "pillow"


Protection elements


 Toecap "Alu Sxt 2.0" with
 differentiated thicknesses, resistant
 to 200J. Non metal perforation
 resistant Insert to over 1100 N with a
 3.0 mm truncated cone nail. Protection
 over the entire sole of the foot.
 Flexible and comfortable


Lateral stability

 dynamic **HC** control
 technology

 Ergonomic rigid internal structure. It
 houses the heel into the right seat,
 adjusting the foot support and control
 of the ankle sideways movements. It
 keeps the foot tight to the shoe,
 allowing the perfect fit.


Torsional stability

STABIL•ACTIVE

 Support made of rigid plastic
 material. It stabilizes the heel bone,
 the instep and tarsal joints, without
 altering energy absorption. A support
 for the natural movement of the foot;
 it provides comfort and greater
 stability.


Electrical features


 ESD footwear discharge static
 electricity and avoid damaging
 surrounding objects; they are
 designed in compliance with the
 following standards: IEC EN
 61340-5-1:2016 - IEC EN
 61340-4-3:2018 - IEC EN
 61340-4-5:2018.

Other

DUALMICRO
DUALMICRO

 Double non-slip layer of microfibre,
 resistant up to 200,000 cycles. Makes
 the footwear more comfortable,
 blocking the foot during use.


PU - PU

SOLE 94

SLIP RESISTANCE

EN ISO 20344:2021

BASIC
 CERAMIC WITH
 NALS

FORWARD HEEL SLIP ≥ 0.31	0,34
BACKWARD FOREPART SLIP ≥ 0.36	0,40


SR
 CERAMIC WITH
 GLYCERINE

FORWARD HEEL SLIP ≥ 0.19	0,29
BACKWARD FOREPART SLIP ≥ 0.22	0,40

