



EN ISO 20347:2012


 SKIPPER
AVOLA
 90389-04

OB A E FO SRC
Size: 38-48
Weight: 400 gr.

Fit: 11

Working Environment:
 Food and Chemical industry,
 Ho.Re.Ca., ESD Areas


FEATURES

UPPER
 MicroFiber XPRO

LINING
 Bacteriostatic Teklife 3D

ANTISLIP LINING
 DUALMICRO

INSOLE
 Five 4 Fit

TYPE
 Clogs

SOLE
PU / PU ESD-PLUS SRC
 Double density PU sole, Outer- and in-between sole with ESD compound. For use in contact with sensitive electronic equipment. Light and comfortable, very versatile, highly non-slip SRC Antislip standard.


SRC (SRA+SRB)


 SOLE 94
 PU - PU

SRA CERAMIC + DETERGENT SOLUTION	FLAT ≥ 0.32	0.41
	HEEL (CONTACT ANGLE °) ≥ 0.28	0.38
SRB STEEL + GLYCEROL	FLAT ≥ 0.18	0.26
	HEEL (CONTACT ANGLE °) ≥ 0.13	0.22

EN ISO 20344:2011

TECHNOLOGIES

Removable Insole


Highly breathable and absorbent anatomic insole. Multilayer structure to take advantage of the peculiarities of each component. Dry and with a comfortable memory foam "pillow"

Protection elements


"Occupational" footwear with all the physico-chemical characteristics and the comfort of Sixton footwear. Footwear without safety toecap, with no anti-perforation insert.

Lateral stability


Ergonomic rigid internal structure. It houses the heel into the right seat, adjusting the foot support and control of the ankle sideways movements. It keeps the foot tight to the shoe, allowing the perfect fit.


Torsional stability


Support made of rigid plastic material. It stabilizes the heel bone, the instep and tarsal joints, without altering energy absorption. A support for the natural movement of the foot; it provides comfort and greater stability.


Electrical features


ESD footwear discharge static electricity and avoid damaging surrounding objects; they are designed in compliance with the following standards: IEC EN 61340-5-1:2016 - IEC EN 61340-4-3:2018 - IEC EN 61340-4-5:2018.

Other


Created for those who work in the HORECA sector, H.ABC footwear has new antibacterial components subjected to analysis by accredited laboratories. The results confirm the constant elimination activity of over 80% of bacterial load.

