



EN ISO 20345:2011


 SKIPPER  
**GRINDER**  
 94403-02L

**S3 SRC**
**Size:** 38-48  
**Weight:** 660 gr.

**Fit:** 11

**Working Environment:**  
 Logistics and Light Industry,  
 Components and Automotive,  
 Finishing-off building, ESD Areas


## FEATURES

**UPPER**  
 Printed Drummed Suede Hydro

**LINING**  
 Breezy 3D, two-layers  
 combination

**ANTISLIP LINING**  
 DUALMICRO

**INSOLE**  
 Five 4 Fit

**TOE CAP**  
 Alu SXT 2.0 Toe cap

**RESISTANCE TO PERFORATION**  
 KX Antiperforation PS

**TYPE**  
 Ankle boot

**SOLE**  
**PU / PU ESD-PLUS SRC**  
 Double density PU sole, Outer- and  
 in-between sole with ESD  
 compound. For use in contact with  
 sensitive electronic equipment.  
 Light and comfortable, very  
 versatile, highly non-slip SRC  
 Antislip standard.

## TECHNOLOGIES

**Removable Insole**
**FIVE4FIT**

 Highly breathable and absorbent  
 anatomic insole. Multilayer structure  
 to take advantage of the peculiarities  
 of each component. Dry and with a  
 comfortable memory foam "pillow"

**Protection elements**
**KX** RESISTANT  
 TO 3.0 mm.  
 NAILS

**alu-sxt2.0**  
 aluminium

 Toecap "Alu Sxt 2.0" with  
 differentiated thicknesses, resistant  
 to 200J. Non metal perforation  
 resistant Insert to over 1100 N with a  
 3.0 mm truncated cone nail. Protection  
 over the entire sole of the foot.  
 Flexible and comfortable

**Lateral stability**
**dynamic H C control**  
 technology

 Ergonomic rigid internal structure. It  
 houses the heel into the right seat,  
 adjusting the foot support and control  
 of the ankle sideways movements. It  
 keeps the foot tight to the shoe,  
 allowing the perfect fit.

**Torsional stability**
**STABIL•ACTIVE**

 Support made of rigid plastic  
 material. It stabilizes the heel bone,  
 the instep and tarsal joints, without  
 altering energy absorption. A support  
 for the natural movement of the foot;  
 it provides comfort and greater  
 stability.

**Electrical features**

 ESD footwear discharge static  
 electricity and avoid damaging  
 surrounding objects; they are  
 designed in compliance with the  
 following standards: IEC EN  
 61340-5-1:2016 - IEC EN  
 61340-4-3:2018 - IEC EN  
 61340-4-5:2018.

**Other**
**DUALMICRO**  
 DUALMICRO

 Double non-slip layer of microfibre,  
 resistant up to 200,000 cycles. Makes  
 the footwear more comfortable,  
 blocking the foot during use.


## SRC (SRA+SRB)



| SOLE 94<br>PU - PU                                  |  |             |
|---|--|-------------|
| <b>SRA</b><br>CERAMIC<br>+<br>DETERGENT<br>SOLUTION | FLAT<br>≥0.32<br>HEEL<br>(CONTACT ANGLE 7°)<br>≥0.28 | <b>0.41</b> |
| <b>SRB</b><br>STEEL<br>+<br>GLYCEROL                | FLAT<br>≥0.18<br>HEEL<br>(CONTACT ANGLE 7°)<br>≥0.13 | <b>0.26</b> |
|   |  | <b>0.22</b> |

EN ISO 20344:2011