



EN ISO 20347:2012



SKIPPER
ROCK
90182-10L

03 FO SRC

Size: 38-48
Weight: 520 gr.

Fit: 11

Working Environment:
Multipurpose, Components and
Automotive, Inclined roofs



FEATURES

TOMAIA

Nubuk Leather Hydro 1,6-1,8 mm

FODERA

3D Air circulation 320 gr.

FOD. ANTISCIVOLO

DUALMICRO

SUOLETTA

Five 4 Fit

RESISTENZA ALLA PERFORAZIONE

Zero(K) Perforation resistant

TIPOLOGIA

Ankle boot

SUOLA

PU DUAL-DENSITY SRC

Double density PU outsole with tread designed mainly for indoor use. Self-cleaning design and highly non-slip grip. SRC Antislip standard.

TECNOLOGIE

Suoletta Intercambiabile



Highly breathable and absorbent anatomic insole. Multilayer structure to take advantage of the peculiarities of each component. Dry and with a comfortable memory foam "pillow"



Protection elements

ZERO(k)
ANTIPERFORATION



"Occupational" footwear with all the physico-chemical characteristics and the comfort of Sixton footwear. Footwear without safety toe cap, with non metallic anti-perforation insert. Resistant to over 1100 N with zero perforation.



SRC (SRA+SRB)



SOLE 94 PU - PU		
SRA CERAMIC + DETERGENT SOLUTION	FLAT ≥0.32	0.41
	HEEL (CONTACT ANGLE °) ≥0.28	0.38
SRB STEEL + GLYCEROL	FLAT ≥0.18	0.26
	HEEL (CONTACT ANGLE °) ≥0.13	0.22

EN ISO 20344:2011

Lateral stability

dynamic **HC** control
technology

Ergonomic rigid internal structure. It houses the heel into the right seat, adjusting the foot support and control of the ankle sideways movements. It keeps the foot tight to the shoe, allowing the perfect fit.



Electrical features

WED

Wire Electricity Discharge

Strip with 4 filaments of carbon fiber, ensuring proven anti-static properties of the footwear over time.



Torsional stability

STABIL•ACTIVE

Support made of rigid plastic material. It stabilizes the heel bone, the instep and tarsal joints, without altering energy absorption. A support for the natural movement of the foot; it provides comfort and greater stability.



Other

**DUALMICRO
DUALMICRO**

Double non-slip layer of microfibre, resistant up to 200,000 cycles. Makes the footwear more comfortable, blocking the foot during use.