



EN ISO 20347:2022



SKIPPER LADY

ALA

96429-01

OBAEFO SR

Size: 35-42 Lady

Weight: 285 gr.

Fit: 11

Working Environment:
Food and Chemical industry,
Ho.Re.Ca., ESD Areas



FEATURES

UPPER

MicroFiber XPRO 1,8-2,0 mm

LINING

Bacteriostatic Teklife 3D

ANTISLIP LINING

DUALMICRO

INSOLE

Five 4 Fit "lady"

TYPE

Clogs

SOLE

PU / PU ESD-PLUS SRC

Double density PU sole, Outer- and in-between sole with ESD compound. For use in contact with sensitive electronic equipment. Light and comfortable, very versatile, highly non-slip



TECHNOLOGIES

Removable Insole



Highly breathable and absorbent anatomic insole. Multilayer structure to take advantage of the peculiarities of each component. Dry and with a comfortable memory foam "pillow"



Protection elements



"Occupational" footwear with all the physico-chemical characteristics and the comfort of Sixton footwear. Footwear without safety toecap, with no anti-perforation insert.

Lateral stability



Ergonomic rigid internal structure. It houses the heel into the right seat, adjusting the foot support and control of the ankle sideways movements. It keeps the foot tight to the shoe, allowing the perfect fit.



Torsional stability



Support made of rigid plastic material. It stabilizes the heel bone, the instep and tarsal joints, without altering energy absorption. A support for the natural movement of the foot; it provides comfort and greater stability.



Electrical features



Wire Electricity Discharge


Strip with 4 filaments of carbon fiber, ensuring proven anti-static properties of the footwear over time.



Other



Created for those who work in the HORECA sector, H.ABC footwear has new antibacterial components subjected to analysis by accredited laboratories. The results confirm the constant elimination activity of over 80% of bacterial load.



PU - PU SOLE 95	SLIP RESISTANCE	
	EN ISO 20344:2021	
BASIC CERAMIC WITH NALS	FORWARD HEEL SLIP ≥ 0.31	0,32
	BACKWARD FOREPART SLIP ≥ 0.36	0,39
SR CERAMIC WITH GLYCERINE	FORWARD HEEL SLIP ≥ 0.19	0,26
	BACKWARD FOREPART SLIP ≥ 0.22	0,30