



EN ISO 20347:2012



SKIPPER LADY

ALA
96429-02
OB A E FO SRC
Size: 35-42 Lady

Weight: 285 gr.

Fit: 11

Working Environment:
 Food and Chemical industry,
 Ho.Re.Ca., ESD Areas


FEATURES

UPPER

MicroFiber XPRO 1,8-2,0 mm

LINING

Bacteriostatic Teklife 3D

ANTISLIP LINING

DUALMICRO

INSOLE

Five 4 Fit "lady"

TYPE

Clogs

SOLE

PU / PU ESD-PLUS SRC

Double density PU sole, Outer- and in-between sole with ESD compound. For use in contact with sensitive electronic equipment. Light and comfortable, very versatile, highly non-slip SRC Antislip standard.



SRC (SRA+SRB)


 SOLE 95
 PU - PU

| | | |
|---|---|-------------|
| SRA CERAMIC + DETERGENT SOLUTION | FLAT ≥0.32 HEEL (CONTACT ANGLE °) ≥0.28 | 0.38 |
| SRB STEEL + GLYCEROL | FLAT ≥0.18 HEEL (CONTACT ANGLE °) ≥0.13 | 0.21 |

EN ISO 20344:2011

TECHNOLOGIES

Removable Insole



Highly breathable and absorbent anatomic insole. Multilayer structure to take advantage of the peculiarities of each component. Dry and with a comfortable memory foam "pillow"



Protection elements



Puncture resistant recycled non-metallic insert plus 1100N.

Lateral stability

dynamic HC control
 technology

Ergonomic rigid internal structure. It houses the heel into the right seat, adjusting the foot support and control of the ankle sideways movements. It keeps the foot tight to the shoe, allowing the perfect fit.



Torsional stability



Support made of rigid plastic material. It stabilizes the heel bone, the instep and tarsal joints, without altering energy absorption. A support for the natural movement of the foot; it provides comfort and greater stability.



Electrical features



ESD footwear discharge static electricity and avoid damaging surrounding objects; they are designed in compliance with the following standards: IEC EN 61340-5-1:2016 - IEC EN 61340-4-3:2018 - IEC EN 61340-4-5:2018.

Other



Created for those who work in the HORECA sector, H.ABC footwear has new antibacterial components subjected to analysis by accredited laboratories. The results confirm the constant elimination activity of over 80% of bacterial load.

