



SOLE

**PU / PU ESD-PLUS SRC** 

in-between sole with ESD

Light and comfortable, very

Antislip standard.

versatile, highly non-slip SRC

sensitive electronic equipment.

# TECHNOLOGIES

# Removable Insole



Highly breathable and absorbent anatomic insole.Multilayer structure to take advantage of the peculiarities of each component. Dry and with a comfortable memory foam "pillow"



### Lateral stability

dynamic H Control technology

Ergonomic rigid internal structure. It houses the heel into the right seat, adjusting the foot support and control of the ankle sideways movements. It keeps the foot tight to the shoe, allowing the perfect fit.

### **Electrical features**



ESD footwear discharge static electricity and avoid damaging surrounding objects; they are designed in compliance with the following standards: IEC EN 61340-5-1:2016 - IEC EN 61340-4-3:2018 - IEC EN 61340-4-5:2018.

### EN ISO 20345:2011

SKIPPER LADY

ALBA HIGH 95442-01

S2 \*CI SRC

Size: 35-42 Lady Weight: 400 gr.

Fit: 11

### Working Environment: Food and Chemical industry Ho.Re.Ca., Multipurpose, ESD Areas



### **Protection elements**




The result of the evolution of the latest aluminium technologies. A new multi-thicknesses toe cap, which delivers a highly performing protection where needed. Ultralight protection, keeping comfortable inner volumest.



Support made of rigid plastic material. It stabilizes the heel bone, the instep and tarsal joints, without altering energy absorption. A support for the natural movement of the foot; it provides comfort and greater . stability



Created for those who work in the HORECA sector, H.ABC footwear has new antibacterial components subjected to analysis by accredited laboratories. The results confirm the constant elimination activity of over 80% of bacterial load.



30/04/2025

M

## **FEATURES**

UPPER

MicroFiber XPRO 1,8-2,0 mm

LINING Bacteriostatic Teklife 3D

ANTISLIP LINING DUALMICRO INSOLE

Five 4 Fit "lady"

TOE CAP Alu SXT 2.0 Toe cap

ТҮРЕ Ankle boot



# SRC (SRA+SRB)

(Minno)	(mm)	SOLE 95 <b>PU - PU</b>	
SRA CERAMIC + DETERGENT SOLUTION	FLAT ≥ <b>0.32</b> HEEL (CONTACT ANGLE ?*) ≥ <b>0.28</b>	0.38 0.34	
STEEL STEEL GLYCEROL	FLAT ≥0.18 HEEL (CONTRACTANGLE ?*) ≥0.13	0.21 0.24	EN ISO 20344:2011







