



EN ISO 20345:2022/A1:2024



SKIPPER LADY
BELVEDERE
95416-01

S1 FO SR

Size: 35-42 Lady
Weight: 415 gr.

Fit: 11

Working Environment:
Logistics and Light Industry,
Components and Automotive, ESD
Areas



FEATURES

UPPER

MicroFiber Suede 1,6-1,8 mm
Digitex Airy
Breezy 3D, two-layers
combination
MicroFiber Suede with Pro-tech
SXT light 1,6-1,8 mm

LINING

Breezy 3D, two-layers
combination

ANTISLIP LINING DUALMICRO

INSOLE

Five 4 Fit "lady"

TOE CAP

Alu SXT 2.0 Toe cap

TYPE

Sandal

SOLE

PU DUAL-DENSITY SRC

Double density PU outsole with
tread designed mainly for indoor
use. Self-cleaning design and
highly non-slip grip.

TECHNOLOGIES

Removable Insole



Highly breathable and absorbent
anatomic insole. Multilayer structure
to take advantage of the peculiarities
of each component. Dry and with a
comfortable memory foam "pillow"



Protection elements



The result of the evolution of the
latest aluminium technologies. A new
multi-thicknesses toe cap, which
delivers a highly performing
protection where needed. Ultralight
protection, keeping comfortable inner
volumest.



Lateral stability



Ergonomic rigid internal structure. It
houses the heel into the right seat,
adjusting the foot support and control
of the ankle sideways movements. It
keeps the foot tight to the shoe,
allowing the perfect fit.



Torsional stability



Support made of rigid plastic
material. It stabilizes the heel bone,
the instep and tarsal joints, without
altering energy absorption. A support
for the natural movement of the foot;
it provides comfort and greater
stability.



Electrical features



ESD footwear discharge static
electricity and avoid damaging
surrounding objects; they are
designed in compliance with the
following standards: IEC EN
61340-5-1:2016 - IEC EN
61340-4-3:2018 - IEC EN
61340-4-5:2018.

Other

Strip with 4 filaments of carbon fiber,
ensuring proven anti-static properties
of the footwear over time.



PU - PU

SOLE 95

SLIP RESISTANCE

EN ISO 20344:2021

BASIC CERAMIC WITH NALS

FORWARD HEEL SLIP ≥ 0,31	0,32	
BACKWARD FOREPART SLIP ≥ 0,36	0,39	

SR CERAMIC WITH GLYCERINE

FORWARD HEEL SLIP ≥ 0,19	0,26	
BACKWARD FOREPART SLIP ≥ 0,22	0,30	