



EN ISO 20345:2011

SKIPPER LADY

BOMA
95401-05L
S3 SRC
Size: 35-42 Lady

Weight: 440 gr.

Fit: 11

Working Environment:

Finishing-off building, Logistics
and Light Industry, ESD Areas,
Multipurpose


FEATURES

UPPER

MicroFiber Suede 1,6-1,8 mm
Microfiber Glitter Xtop

LINING

Breezy 3D, two-layers
combination

ANTISLIP LINING

DUALMICRO

INSOLE

Five 4 Fit "lady"

TOE CAP

Alu SXT 2.0 Toe cap

RESISTANCE TO PERFORATION

KX Antiperforation PS

TYPE

Low Shoe

SOLE

PU DUAL-DENSITY SRC


Double density PU outsole with
tread designed mainly for indoor
use. Self-cleaning design and
highly non-slip grip. SRC Antislip
standard.

TECHNOLOGIES

Removable Insole


Highly breathable and absorbent
anatomic insole. Multilayer structure
to take advantage of the peculiarities
of each component. Dry and with a
comfortable memory foam "pillow"


Protection elements


Composite toecap with fiberglass.
Resistant to over 200J. Non metal
perforation resistant insert to over
1100 N with a 3.0 mm truncated cone
nail. Protection over the entire sole of
the foot. Flexible and comfortable


Lateral stability

dynamic **HC** control
technology

Ergonomic rigid internal structure. It
houses the heel into the right seat,
adjusting the foot support and control
of the ankle sideways movements. It
keeps the foot tight to the shoe,
allowing the perfect fit.


Torsional stability

Support made of rigid plastic
material. It stabilizes the heel bone,
the instep and tarsal joints, without
altering energy absorption. A support
for the natural movement of the foot;
it provides comfort and greater
stability.


Electrical features


ESD footwear discharge static
electricity and avoid damaging
surrounding objects; they are
designed in compliance with the
following standards: IEC EN
61340-5-1:2016 - IEC EN
61340-4-3:2018 - IEC EN
61340-4-5:2018.

Other


Double non-slip layer of microfibre,
resistant up to 200,000 cycles. Makes
the footwear more comfortable,
blocking the foot during use.


SRC (SRA+SRB)


SOLE 95
PU - PU

| | | |
|---|--|-------------|
| SRA CERAMIC + DETERGENT SOLUTION | FLAT ≥0.32 HEEL (CONTACT ANGLE °°) ≥0.28 | 0.38 |
| SRB STEEL + GLYCEROL | FLAT ≥0.18 HEEL (CONTACT ANGLE °°) ≥0.13 | 0.21 |
| | | 0.24 |

EN ISO 20344:2011