sixton SAFETY SHOES peak





EN ISO 20345:2022+A1:2024

SKIPPER LADY

CIMA BOA®

95582-00L

S3S FO SR

Size: 35-42 Lady
Weight: 425 gr.

Fit: 11

Working Environment:
Logistics and Light Industry, Components and Automotive, ESD Areas

FEATURES

UPPER
MicroFiber Suede 1,6-1,8 mm

LINING
3D Green Air 320 gr.

ANTISLIP LINING
DUALMICRO

INSOLE
Five 4 Fit "lady"

TOE CAP

RESISTANCE TO PERFORATION
KX Antiperforation PS

TYPE
Low Shoe

SOLE
PU DUAL-DENSITY SRC
Double density PU outsole with tread designed mainly for indoor use. Self-cleaning design and highly non-slip grip.

Boa® lace length
L6 - 60CM

S | A | E | FO | WPA | PS | SR

PU - PU SOLE 95		SLIP RESISTANCE EN ISO 20344:2021	
BASIC CERAMIC WITH NALS	FORWARD HEEL SLIP ≥ 0.31	0,32	
	BACKWARD FOREPART SLIP ≥ 0.36	0,39	
SR CERAMIC WITH GLYCERINE	FORWARD HEEL SLIP ≥ 0.19	0,26	
	BACKWARD FOREPART SLIP ≥ 0.22	0,30	

TECHNOLOGIES

Removable Insole

FIVE4FIT LADY

Highly breathable and absorbent anatomic insole.Multilayer structure to take advantage of the peculiarities of each component. Dry and with a comfortable memory foam "pillow"



Protection elements

KX RESISTANT TO 3.0 mm. NAILS

alu-sxt 2.0 aluminium

Toecap "Alu Sxt 2.0" with differentiated thicknesses, resistant to 200J. Non metal perforation resistant Insert to over 1100 N with a 3.0 mm truncated cone nail.Protection over the entire sole of the foot. Flexible and comfortable



Lateral stability

dynamic HC control technology

Ergonomic rigid internal structure. It houses the heel into the right seat, adjusting the foot support and control of the ankle sideways movements. It keeps the foot tight to the shoe, allowing the perfect fit.



Torsional stability

STABIL•ACTIVE

Support made of rigid plastic material. It stabilizes the heel bone, the instep and tarsal joints, without altering energy absorption. A support for the natural movement of the foot; it provides comfort and greater stability.



Electrical features

ESD

ESD footwear discharge static electricity and avoid damaging surrounding objects; they are designed in compliance with the following standards: IEC EN 61340-5-1:2016 - IEC EN 61340-4-3:2018 - IEC EN 61340-4-5:2018.

Other

BOA | FIT TO GO FURTHER.™

A patented closing system with a multi coated stainless steel cable. The BOA® Fit System delivers micro-adjustable precision fit, engineered to perform in the toughest conditions.



Maspica Srl a Socio Unico Via Einstein,6 - 35020 Casalserugo - Padova / Italy - Cap. Soc. 1.050.000 i.v. - cod. fisc. e Reg. Imp. 04009100282 p. iva IT04009100282
C.C.I.A.A./R.E.A.354572 tel. +39 049 8740771 fax +39 049 8741376 www.sixton.it - info@maspica.it

Questo documento è di proprietà di Maspica Srl a Socio Unico, che si riserva di modificarne i contenuti. È vietata ogni riproduzione, anche parziale