



EN ISO 20347:2012



SKIPPER LADY

**CIMA**
**96398-05**
**02 FO SRC**
**Size:** 35-42 Lady

**Weight:** 360 gr.

**Fit:** 11

**Working Environment:**

Multipurpose, Components and Automotive



## FEATURES

### UPPER

Digitex Hydro Airy  
 MicroFiber Suede 1,6-1,8 mm  
 Digitex Hydro Airy  
 MicroFiber Suede with Pro-tech  
 SXT light 1,6-1,8 mm

### LINING

Breezy 3D, two-layers  
 combination

### ANTISLIP LINING

DUALMICRO

### INSOLE

Five 4 Fit

### TOE CAP

### TYPE

Low Shoe

### SOLE

#### PU DUAL-DENSITY SRC

Double density PU outsole with tread designed mainly for indoor use. Self-cleaning design and highly non-slip grip. SRC Antislip standard.

## TECHNOLOGIES

### Removable Insole

**FIVE 4 FIT**

Highly breathable and absorbent anatomic insole. Multilayer structure to take advantage of the peculiarities of each component. Dry and with a comfortable memory foam "pillow"



### Protection elements



**EN ISO 20347:2012**

Puncture resistant recycled non-metallic insert plus 1100N.

### Lateral stability

**dynamic HC control**  
 technology

Ergonomic rigid internal structure. It houses the heel into the right seat, adjusting the foot support and control of the ankle sideways movements. It keeps the foot tight to the shoe, allowing the perfect fit.



### Torsional stability



**STABIL ACTIVE**  
 Support made of rigid plastic material. It stabilizes the heel bone, the instep and tarsal joints, without altering energy absorption. A support for the natural movement of the foot; it provides comfort and greater stability.



### Electrical features



ESD footwear discharge static electricity and avoid damaging surrounding objects; they are designed in compliance with the following standards: IEC EN 61340-5-1:2016 - IEC EN 61340-4-3:2018 - IEC EN 61340-4-5:2018.

### Other

**DUAL MICRO DWT WICBO**

Double non-slip layer of microfibre, resistant up to 200,000 cycles. Makes the footwear more comfortable, blocking the foot during use.



## SRC (SRA+SRB)



SOLE 95  
 PU - PU

SRA CERAMIC + DETERGENT SOLUTION	FLAT ≥0.32	0.38
	HEEL (CONTACT ANGLE °°) ≥0.28	0.34
SRB STEEL + GLYCEROL	FLAT ≥0.18	0.21
	HEEL (CONTACT ANGLE °°) ≥0.13	0.24

EN ISO 20344:2011