




EN ISO 20345:2011 


SKIPPER LADY
CIMA
95398-03L

S1P SRC

Size: 35-42 Lady
Weight: 420 gr.

Fit: 11

Working Environment:
 Logistics and Light Industry,
 Components and Automotive,
 Wood-metal carpentry, ESD Areas



FEATURES

UPPER
 Digitex Airy
 MicroFiber Suede with Pro-tech
 SXT light

LINING
 Breezy 3D, two-layers
 combination

ANTISLIP LINING
 DUALMICRO


INSOLE
 Five 4 Fit "lady"

TOE CAP
 Alu SXT 2.0 Toe cap



RESISTANCE TO PERFORATION
 Textile resistant to 3.0 mm nail - X
 Method

TYPE
 Low Shoe

SOLE
PU DUAL-DENSITY SRC
 Double density PU outsole with
 tread designed mainly for indoor
 use. Self-cleaning design and
 highly non-slip grip. SRC Antislip
 standard.



SRC (SRA+SRB)

		SOLE 95 PU - PU
SRA CERAMIC + DETERGENT SOLUTION	FLAT ≥0.32 HEEL (CONTACT ANGLE °) ≥0.28	0.38
		0.34
SRB STEEL + GLYCEROL	FLAT ≥0.18 HEEL (CONTACT ANGLE °) ≥0.13	0.21
		0.24

EN ISO 20344:2011

TECHNOLOGIES


Removable Insole



Highly breathable and absorbent
 anatomic insole. Multilayer structure
 to take advantage of the peculiarities
 of each component. Dry and with a
 comfortable memory foam "pillow"



Protection elements



Toecap "Alu Sxt 2.0" with
 differentiated thicknesses, resistant
 to 200J. Non metal perforation
 resistant Insert to over 1100 N with a
 3.0 mm truncated cone nail. Protection
 over the entire sole of the foot.
 Flexible and comfortable



Lateral stability



Ergonomic rigid internal structure. It
 houses the heel into the right seat,
 adjusting the foot support and control
 of the ankle sideways movements. It
 keeps the foot tight to the shoe,
 allowing the perfect fit.



Torsional stability



Support made of rigid plastic
 material. It stabilizes the heel bone,
 the instep and tarsal joints, without
 altering energy absorption. A support
 for the natural movement of the foot;
 it provides comfort and greater
 stability.



Electrical features



ESD footwear discharge static
 electricity and avoid damaging
 surrounding objects; they are
 designed in compliance with the
 following standards: IEC EN
 61340-5-1:2016 - IEC EN
 61340-4-3:2018 - IEC EN
 61340-4-5:2018.

Other

The microfibre/ fabric of the toe cap is
 protected by the application of pro-
 tech SXT polyurethane to increase the
 resistance of the upper over time. This
 shoe is recommended for "light" work
 environments.

