



EN ISO 20345:2022/A1:2024



SKIPPER LADY

CIMA

95398-03L

S1PS FO SR

Size: 35-42 Lady

Weight: 420 gr.

Fit: 11

Working Environment:

Logistics and Light Industry,
Components and Automotive,
Wood-metal carpentry, ESD Areas



FEATURES

UPPER

Digitex Airy
MicroFiber Suede with Pro-tech
SXT light 1,6-1,8 mm

LINING

Breezy 3D, two-layers
combination

ANTISLIP LINING

DUALMICRO

INSOLE

Five 4 Fit "lady"

TOE CAP

Alu SXT 2.0 Toe cap

RESISTANCE TO PERFORATION

KX Antiperforation PS

TYPE

Low Shoe

SOLE

PU DUAL-DENSITY SRC

Double density PU outsole with
tread designed mainly for indoor
use. Self-cleaning design and
highly non-slip grip.

TECHNOLOGIES

Removable Insole



Highly breathable and absorbent
anatomic insole. Multilayer structure
to take advantage of the peculiarities
of each component. Dry and with a
comfortable memory foam "pillow"

Protection elements



Toecap "Alu Sxt 2.0" with
differentiated thicknesses, resistant
to 200J. Non metal perforation
resistant Insert to over 1100 N with a
3.0 mm truncated cone nail. Protection
over the entire sole of the foot.
Flexible and comfortable



Lateral stability



Ergonomic rigid internal structure. It
houses the heel into the right seat,
adjusting the foot support and control
of the ankle sideways movements. It
keeps the foot tight to the shoe,
allowing the perfect fit.

Torsional stability



Support made of rigid plastic
material. It stabilizes the heel bone,
the instep and tarsal joints, without
altering energy absorption. A support
for the natural movement of the foot;
it provides comfort and greater
stability.



Electrical features



ESD footwear discharge static
electricity and avoid damaging
surrounding objects; they are
designed in compliance with the
following standards: IEC EN
61340-5-1:2016 - IEC EN
61340-4-3:2018 - IEC EN
61340-4-5:2018.

Other

The microfibre/ fabric of the toe cap is
protected by the application of pro-
tech SXT polyurethane to increase the
resistance of the upper over time. This
shoe is recommended for "light" work
environments.



PU - PU

SOLE 95

SLIP RESISTANCE

EN ISO 20344:2021

BASIC CERAMIC WITH NAILS

FORWARD HEEL SLIP ≥ 0.31	0,32	
BACKWARD FOREPART SLIP ≥ 0.36	0,39	

SR CERAMIC WITH GLYCERINE

FORWARD HEEL SLIP ≥ 0.19	0,26	
BACKWARD FOREPART SLIP ≥ 0.22	0,30	