sixton SAFETY SHOES peak

EN ISO 20345:2022+A1:2024

SKIPPER LADY

CIMA

95398-03L

S1PS FO SR

Size: 35-42 Lady
Weight: 420 gr.

Fit: 11

Working Environment:
Logistics and Light Industry, Components and Automotive, Wood-metal carpentry, ESD Areas

FEATURES

UPPER
Digitex Airy
MicroFiber Suede with Pro-tech SXT light 1,6-1,8 mm

LINING
Breezy 3D, two-layers combination

ANTISLIP LINING
DUALMICRO

INSOLE
Five 4 Fit "lady"

TOE CAP
Alu SXT 2.0 Toe cap

RESISTANCE TO PERFORATION
KX Antiperforation PS

TYPE
Low Shoe

SOLE
PU DUAL-DENSITY SRC
Double density PU outsole with tread designed mainly for indoor use. Self-cleaning design and highly non-slip grip.

S A E FO AIRY PS SR

PU - PU
SOLE 95

			SLIP RESISTANCE EN ISO 20344:2021
BASIC CERAMIC WITH NALS	FORWARD HEEL SLIP ≥ 0.31	0,32	
	BACKWARD FOREPART SLIP ≥ 0.36	0,39	
SR CERAMIC WITH GLYCERINE	FORWARD HEEL SLIP ≥ 0.19	0,26	
	BACKWARD FOREPART SLIP ≥ 0.22	0,30	

TECHNOLOGIES

Removable Insole

FIVE4FIT LADY

Highly breathable and absorbent anatomic insole.Multilayer structure to take advantage of the peculiarities of each component. Dry and with a comfortable memory foam "pillow"

Protection elements

KX RESISTANT TO 3.0 mm. NAILS

alu-sxt 2.0 aluminium

Toecap "Alu Sxt 2.0" with differentiated thicknesses, resistant to 200J. Non metal perforation resistant Insert to over 1100 N with a 3.0 mm truncated cone nail.Protection over the entire sole of the foot. Flexible and comfortable

Lateral stability

dynamic HC control technology

Ergonomic rigid internal structure. It houses the heel into the right seat, adjusting the foot support and control of the ankle sideways movements. It keeps the foot tight to the shoe, allowing the perfect fit.

Torsional stability

STABIL•ACTIVE

Support made of rigid plastic material. It stabilizes the heel bone, the instep and tarsal joints, without altering energy absorption. A support for the natural movement of the foot; it provides comfort and greater stability.

Electrical features

ESD footwear discharge static electricity and avoid damaging surrounding objects; they are designed in compliance with the following standards: IEC EN 61340-5-1:2016 - IEC EN 61340-4-3:2018 - IEC EN 61340-4-5:2018.

Other

The microfibe/ fabric of the toe cap is protected by the application of pro-tech SXT polyurethane to increase the resistance of the upper over time.This shoe is recommended for "light" work environments.

Maspica Srl a Socio Unico Via Einstein,6 - 35020 Casalserugo - Padova / Italy - Cap. Soc. 1.050.000 i.v. - cod. fisc. e Reg. Imp. 04009100282 p. iva IT04009100282
C.C.I.A.A./R.E.A.354572 tel. +39 049 8740771 fax +39 049 8741376 www.sixton.it - info@maspica.it

Questo documento è di proprietà di Maspica Srl a Socio Unico, che si riserva di modificarne i contenuti. È vietata ogni riproduzione, anche parziale