




**EN ISO 20345:2011** 


**SKIPPER LADY**  
**CIMA**  
**95398-02L**

**S3 SRC**

**Size:** 35-42 Lady  
**Weight:** 420 gr.

**Fit:** 11

**Working Environment:**  
Logistics and Light Industry,  
Components and Automotive, ESD  
Areas



## FEATURES

### UPPER

Digitex Hydro Airy  
MicroFiber Suede with Pro-tech  
SXT light

### LINING

Breezy 3D, two-layers  
combination

### ANTISLIP LINING

DUALMICRO

### INSOLE

Five 4 Fit "lady"

### TOE CAP

Alu SXT 2.0 Toe cap

### RESISTANCE TO PERFORATION

Textile resistant to 3.0 mm nail

### TYPE

Low Shoe

### SOLE

#### PU DUAL-DENSITY SRC

Double density PU outsole with  
tread designed mainly for indoor  
use. Self-cleaning design and  
highly non-slip grip. SRC Antislip  
standard.

## TECHNOLOGIES

### Removable Insole



Highly breathable and absorbent  
anatomic insole. Multilayer structure  
to take advantage of the peculiarities  
of each component. Dry and with a  
comfortable memory foam "pillow"

### Protection elements



Aluminium toe cap "Alu Sxt 2.0" with  
differentiated functional  
thicknesses, and compensation  
rubber. Resistant to 200J. And Non  
metallic "K+ Insole", tested with  
carpenter nail of diameter 2.8 mm,  
with pyramidal trunk tip



### Lateral stability



Ergonomic rigid internal structure. It  
houses the heel into the right seat,  
adjusting the foot support and control  
of the ankle sideways movements. It  
keeps the foot tight to the shoe,  
allowing the perfect fit.

### Torsional stability



Support made of rigid plastic  
material. It stabilizes the heel bone,  
the instep and tarsal joints, without  
altering energy absorption. A support  
for the natural movement of the foot;  
it provides comfort and greater  
stability.



### Electrical features



ESD footwear discharge static  
electricity and avoid damaging  
surrounding objects; they are  
designed in compliance with the  
following standards: IEC EN  
61340-5-1:2016 - IEC EN  
61340-4-3:2018 - IEC EN  
61340-4-5:2018.

### Other



Double non-slip layer of microfibre,  
resistant up to 200,000 cycles. Makes  
the footwear more comfortable,  
blocking the foot during use.



## SRC (SRA+SRB)



SRA CERAMIC + DETERGENT SOLUTION	FLAT ≥0.32	0.38
	HEEL (CONTACT ANGLE °) ≥0.28	
SRB STEEL + GLYCEROL	FLAT ≥0.18	0.21
	HEEL (CONTACT ANGLE °) ≥0.13	

EN ISO 20344:2011