



EN ISO 20345:2011



SKIPPER LADY

**WINDEX HIGH**
**95414-00L**
**S3 SRC**
**Size:** 35-42 Lady

**Weight:** 430 gr.

**Fit:** 11

**Working Environment:**

 Logistics and Light Industry,  
 Finishing-off building,  
 Components and Automotive, ESD  
 Areas


## FEATURES

### UPPER

 Grain leather Hydro 1,6-1,8 mm  
 Fabric of High Tenacity  
 Fabric of High Tenacity  
 Reflex insert

### LINING

3D Air circulation 320 gr.

### ANTISLIP LINING

DUALMICRO

### INSOLE

Five 4 Fit "lady"

### TOE CAP

Alu SXT 2.0 Toe cap

### RESISTANCE TO PERFORATION

KX Antiperforation PS

### TYPE

Ankle boot

### SOLE

#### PU DUAL-DENSITY SRC

 Double density PU outsole with  
 tread designed mainly for indoor  
 use. Self-cleaning design and  
 highly non-slip grip. SRC Antislip  
 standard.

## TECHNOLOGIES

### Removable Insole


 Highly breathable and absorbent  
 anatomic insole. Multilayer structure  
 to take advantage of the peculiarities  
 of each component. Dry and with a  
 comfortable memory foam "pillow"

### Protection elements


 RESISTANT  
 TO 3.0 mm.  
 NAILS

**alu-sxt2.0**  
 aluminium

 Toecap "Alu Sxt 2.0" with  
 differentiated thicknesses, resistant  
 to 200J. Non metal perforation  
 resistant Insert to over 1100 N with a  
 3.0 mm truncated cone nail. Protection  
 over the entire sole of the foot.  
 Flexible and comfortable


### Lateral stability

**dynamic H C control**  
 technology

 Ergonomic rigid internal structure. It  
 houses the heel into the right seat,  
 adjusting the foot support and control  
 of the ankle sideways movements. It  
 keeps the foot tight to the shoe,  
 allowing the perfect fit.

### Torsional stability

**STABIL • ACTIVE**

 Support made of rigid plastic  
 material. It stabilizes the heel bone,  
 the instep and tarsal joints, without  
 altering energy absorption. A support  
 for the natural movement of the foot;  
 it provides comfort and greater  
 stability.


### Electrical features


 ESD footwear discharge static  
 electricity and avoid damaging  
 surrounding objects; they are  
 designed in compliance with the  
 following standards: IEC EN  
 61340-5-1:2016 - IEC EN  
 61340-4-3:2018 - IEC EN  
 61340-4-5:2018.

### Other

**DUALMICRO**  
**DUALMICRO**

 Double non-slip layer of microfibre,  
 resistant up to 200,000 cycles. Makes  
 the footwear more comfortable,  
 blocking the foot during use.


## SRC (SRA+SRB)


 SOLE 95  
 PU - PU

SRA CERAMIC + DETERGENT SOLUTION	FLAT ≥0.32	0.38
	HEEL (CONTACT ANGLE 7°) ≥0.28	0.34
SRB STEEL + GLYCEROL	FLAT ≥0.18	0.21
	HEEL (CONTACT ANGLE 7°) ≥0.13	0.24

EN ISO 20344:2011