



EN ISO 20345:2022/A1:2024 

SKIPPER LADY
WINDEX HIGH
95414-00L

S3S FO *CI SR

Size: 35-42 Lady
Weight: 430 gr.

Fit: 11

Working Environment:
Logistics and Light Industry,
Finishing-off building,
Components and Automotive, ESD
Areas



FEATURES

UPPER

Grain leather Hydro 1,6-1,8 mm
Fabric of High Tenacity
Fabric of High Tenacity
Reflex insert

LINING

3D Air circulation 320 gr.

ANTISLIP LINING

DUALMICRO

INSOLE

Five 4 Fit "lady"

TOE CAP

Alu SXT 2.0 Toe cap

RESISTANCE TO PERFORATION

KX Antiperforation PS

TYPE

Ankle boot

SOLE

PU DUAL-DENSITY SRC

Double density PU outsole with tread designed mainly for indoor use. Self-cleaning design and highly non-slip grip.


TECHNOLOGIES

Removable Insole



Highly breathable and absorbent anatomic insole. Multilayer structure to take advantage of the peculiarities of each component. Dry and with a comfortable memory foam "pillow"

Protection elements



Toecap "Alu Sxt 2.0" with differentiated thicknesses, resistant to 200J. Non metal perforation resistant Insert to over 1100 N with a 3.0 mm truncated cone nail. Protection over the entire sole of the foot. Flexible and comfortable



Lateral stability



Ergonomic rigid internal structure. It houses the heel into the right seat, adjusting the foot support and control of the ankle sideways movements. It keeps the foot tight to the shoe, allowing the perfect fit.

Torsional stability



Support made of rigid plastic material. It stabilizes the heel bone, the instep and tarsal joints, without altering energy absorption. A support for the natural movement of the foot; it provides comfort and greater stability.



Electrical features



ESD footwear discharge static electricity and avoid damaging surrounding objects; they are designed in compliance with the following standards: IEC EN 61340-5-1:2016 - IEC EN 61340-4-3:2018 - IEC EN 61340-4-5:2018.

Other



Double non-slip layer of microfibre, resistant up to 200,000 cycles. Makes the footwear more comfortable, blocking the foot during use.



PU - PU

SOLE 95

SLIP RESISTANCE

EN ISO 20344:2021

	FORWARD HEEL SLIP	BACKWARD FOREPART SLIP	Diagram
BASIC CERAMIC WITH NAILS	≥ 0.31	≥ 0.36	
SR CERAMIC WITH GLYCERINE	≥ 0.19	≥ 0.22	