



EN ISO 20345:2011



SKIPPER LADY
WINDEX
95406-03

S1 SRC

Size: 35-42 Lady
Weight: 420 gr.

Fit: 11

Working Environment:
Logistics and Light Industry,
Components and Automotive, ESD
Areas



FEATURES

UPPER

MicroFiber Suede 1,6-1,8 mm
MicroFiber Suede 1,6-1,8 mm
Cubik Lamé
Reflex insert

LINING

Breezy 3D, two-layers
combination

ANTISLIP LINING

DUALMICRO

INSOLE

Five 4 Fit "lady"

TOE CAP

Alu SXT 2.0 Toe cap


TYPE

Low Shoe

SOLE

PU DUAL-DENSITY SRC

Double density PU outsole with
tread designed mainly for indoor
use. Self-cleaning design and
highly non-slip grip. SRC Antislip
standard.



SRC (SRA+SRB)



SOLE 95
PU - PU

SRA CERAMIC + DETERGENT SOLUTION	FLAT ≥0.32	0.38
	HEEL (CONTACT ANGLE °?) ≥0.28	
SRB STEEL + GLYCEROL	FLAT ≥0.18	0.21
	HEEL (CONTACT ANGLE °?) ≥0.13	

EN ISO 20344:2011

TECHNOLOGIES

Removable Insole



Highly breathable and absorbent
anatomic insole. Multilayer structure
to take advantage of the peculiarities
of each component. Dry and with a
comfortable memory foam "pillow"



Protection elements



The result of the evolution of the
latest aluminium technologies. A new
multi-thicknesses toe cap, which
delivers a highly performing
protection where needed. Ultralight
protection, keeping comfortable inner
volumest.



Lateral stability



Ergonomic rigid internal structure. It
houses the heel into the right seat,
adjusting the foot support and control
of the ankle sideways movements. It
keeps the foot tight to the shoe,
allowing the perfect fit.



Torsional stability



Support made of rigid plastic
material. It stabilizes the heel bone,
the instep and tarsal joints, without
altering energy absorption. A support
for the natural movement of the foot;
it provides comfort and greater
stability.



Electrical features



ESD footwear discharge static
electricity and avoid damaging
surrounding objects; they are
designed in compliance with the
following standards: IEC EN
61340-5-1:2016 - IEC EN
61340-4-3:2018 - IEC EN
61340-4-5:2018.

Other



Double non-slip layer of microfibre,
resistant up to 200,000 cycles. Makes
the footwear more comfortable,
blocking the foot during use.