



EN ISO 20345:2011



TOURING
NISIDA
10037-14L

S3 *CI SRC

Size: 36-48
Weight: 620 gr.

Fit: 11

Working Environment:
Finishing-off building, Logistics and Light Industry, Components and Automotive, Multipurpose



FEATURES

UPPER
Drummed Suede Leather Hydro
1,8-2,0 mm

LINING
3D Air circulation 320 gr.

ANTISLIP LINING
DUALMICRO

INSOLE
Climaction-Fit 337

TOE CAP
Fiber cap SXT

RESISTANCE TO PERFORATION
Textile resistant to 3.0 mm nail

TYPE
Ankle boot

SOLE
PU DUAL-DENSITY SRC
Two-component PU sole. Outsole suitable for indoor and outdoor use. Light and comfortable. Very flexible. Self-cleaning design and highly anti-slip. SRC Antislip Standard.

TECHNOLOGIES

Removable Insole
337 climaction fit

Removable anatomic and ergonomic insole. Absorbent and transpiring open-cell foam support. Keeps feet fresh. Specifically-designed thermoforming for exceptional comfort.



Protection elements
RESISTANT TO 3.0 mm. NAILS **fibercap sxt**

Composite toecap with fiberglass. Resistant to over 200J. Non metal perforation resistant insert to over 1100 N with a 3.0 mm truncated cone nail. Protection over the entire sole of the foot. Flexible and comfortable



Lateral stability
dynamic HC control technology

Ergonomic rigid internal structure. It houses the heel into the right seat, adjusting the foot support and control of the ankle sideways movements. It keeps the foot tight to the shoe, allowing the perfect fit.



Torsional stability
STABIL•ACTIVE

Support made of rigid plastic material. It stabilizes the heel bone, the instep and tarsal joints, without altering energy absorption. A support for the natural movement of the foot; it provides comfort and greater stability.



Electrical features
WED
Wire Electricity Discharge

Strip with 4 filaments of carbon fiber, ensuring proven anti-static properties of the footwear over time.



Other
DUALMICRO DUALMICRO

Double non-slip layer of microfibre, resistant up to 200,000 cycles. Makes the footwear more comfortable, blocking the foot during use.



SRC (SRA+SRB)

		SOLE TO PU - PU
SRA CERAMIC + DETERGENT SOLUTION	FLAT ≥ 0.32	0.39
	HEEL (CONTACT ANGLE °) ≥ 0.28	0.34
SRB STEEL + GLYCEROL	FLAT ≥ 0.18	0.19
	HEEL (CONTACT ANGLE °) ≥ 0.13	0.14

EN ISO 20344:2011