



EN ISO 20345:2011


 TOURING
NISIDA
 10037-14L

S3 *CI SRC
Size: 36-48
Weight: 620 gr.

Fit: 11

Working Environment:
 Finishing-off building, Logistics
 and Light Industry, Components
 and Automotive, Multipurpose


FEATURES

UPPER

 Drummed Suede Leather Hydro
 1,8-2,0 mm

LINING

3D Air circulation 320 gr.

ANTISLIP LINING DUALMICRO

INSOLE

Climaction-Fit 337

TOE CAP

Fiber cap SXT

RESISTANCE TO PERFORATION

KX Antiperforation PS

TYPE

Ankle boot

SOLE

PU DUAL-DENSITY SRC

 Two-component PU sole. Outsole
 suitable for indoor and outdoor use.
 Light and comfortable. Very
 flexible. Self-cleaning design and
 highly anti-slip. SRC Antislip
 Standard.

TECHNOLOGIES

Removable Insole

337
climaction fit

 Removable anatomic and ergonomic
 insole. Absorbent and transpiring
 open-cell foam support. Keeps feet
 fresh. Specifically-designed
 thermoforming for exceptional
 comfort.


Protection elements


 RESISTANT
 TO 3.0 mm.
 NAILS

fibercap sxt

 Composite toecap with fiberglass.
 Resistant to over 200J. Non metal
 perforation resistant insert to over
 1100 N with a 3.0 mm truncated cone
 nail. Protection over the entire sole of
 the foot. Flexible and comfortable


Lateral stability

dynamic HC control
 technology

 Ergonomic rigid internal structure. It
 houses the heel into the right seat,
 adjusting the foot support and control
 of the ankle sideways movements. It
 keeps the foot tight to the shoe,
 allowing the perfect fit.


Torsional stability



STABIL-ACTIVE

 Support made of rigid plastic
 material. It stabilizes the heel bone,
 the instep and tarsal joints, without
 altering energy absorption. A support
 for the natural movement of the foot;
 it provides comfort and greater
 stability.


Electrical features



Wire Electricity Discharge

 Strip with 4 filaments of carbon fiber,
 ensuring proven anti-static properties
 of the footwear over time.


Other

DUALMICRO
DUALMICRO

 Double non-slip layer of microfibre,
 resistant up to 200,000 cycles. Makes
 the footwear more comfortable,
 blocking the foot during use.


SRC (SRA+SRB)


 SOLE TO
 PU - PU

SRA CERAMIC + DETERGENT SOLUTION	FLAT ≥0.32 HEEL (CONTACT ANGLE °°) ≥0.28	0.39
SRB STEEL + GLYCEROL	FLAT ≥0.18 HEEL (CONTACT ANGLE °°) ≥0.13	0.19
		0.14

EN ISO 20344:2011