



EN ISO 20344:2011



URBAN
CAPRI
82149-01

S1 SRC

Size: 36-48
Weight: 540 gr.

Fit: 11

Working Environment:
Multipurpose, Wood-metal carpentry, Logistics and Light Industry, Components and Automotive



FEATURES

UPPER

Drummed leather Hydro 1,8-2,0 mm

LINING

3D Air circulation 320 gr.

ANTISLIP LINING
DUALMICRO

INSOLE

Climaction-Fit 337

TOE CAP

Fiber cap SXT

TYPE

Low Shoe

SOLE

PU DUAL-DENSITY SRC

Two-component PU outsole with tread designed mainly for indoor use. Self-cleaning design and highly non-slip grip. SRC Antislip standard.

TECHNOLOGIES

Removable Insole

climaction fit 337

Removable anatomic and ergonomic insole. Absorbent and transpiring open-cell foam support. Keeps feet fresh. Specifically-designed thermoforming for exceptional comfort.



Protection elements

fibercap sxt

Composite toecap, reinforced with fiberglass. Structure with a variable thickness for better performances



SRC (SRA+SRB)



		SOLE 82 PU - PU
SRA CERAMIC + DETERGENT SOLUTION	FLAT ≥0.32	0.47
	HEEL (CONTACT ANGLE °) ≥0.28	0.43
SRB STEEL + GLYCEROL	FLAT ≥0.18	0.21
	HEEL (CONTACT ANGLE °) ≥0.13	0.16

EN ISO 20344:2011

Lateral stability

dynamic HC control
technology

Ergonomic rigid internal structure. It houses the heel into the right seat, adjusting the foot support and control of the ankle sideways movements. It keeps the foot tight to the shoe, allowing the perfect fit.



Torsional stability

STABIL•ACTIVE

Support made of rigid plastic material. It stabilizes the heel bone, the instep and tarsal joints, without altering energy absorption. A support for the natural movement of the foot; it provides comfort and greater stability.



Electrical features

WED

Wire Electricity Discharge

Strip with 4 filaments of carbon fiber, ensuring proven anti-static properties of the footwear over time.



Other

DUALMICRO
DUALMICRO

Double non-slip layer of microfibre, resistant up to 200,000 cycles. Makes the footwear more comfortable, blocking the foot during use.