



EN ISO 20345:2011


 URBAN  
**CAPRI**  
 82149-00

**S2 \*CI SRC**
**Size:** 36-48  
**Weight:** 540 gr.

**Fit:** 11

**Working Environment:**  
 Multipurpose, Wood-metal  
 carpentry, Logistics and Light  
 Industry, Components and  
 Automotive


## FEATURES

### UPPER

Drummed leather Hydro 1,8-2,0 mm

### LINING

3D Air circulation 320 gr.

**ANTISLIP LINING**  
 DUALMICRO

### INSOLE

Climaction-Fit 337

### TOE CAP

Fiber cap SXT

### TYPE

Low Shoe

### SOLE

**PU DUAL-DENSITY SRC**

Two-component PU outsole with tread designed mainly for indoor use. Self-cleaning design and highly non-slip grip. SRC Antislip standard.



## SRC (SRA+SRB)

	SOLE 82 PU - PU	
<b>SRA</b> CERAMIC + DETERGENT SOLUTION	FLAT ≥0.32 HEEL (CONTACT ANGLE °) ≥0.28	<b>0.47</b> <b>0.43</b>
<b>SRB</b> STEEL + GLYCEROL	FLAT ≥0.18 HEEL (CONTACT ANGLE °) ≥0.13	<b>0.21</b> <b>0.16</b>

EN ISO 20344:2011

## TECHNOLOGIES

### Removable Insole

**climaction<sup>337</sup> fit**

Removable anatomic and ergonomic insole. Absorbent and transpiring open-cell foam support. Keeps feet fresh. Specifically-designed thermoforming for exceptional comfort.



### Protection elements

**fibercap sxt**

Composite toecap, reinforced with fiberglass. Structure with a variable thickness for better performances



### Lateral stability

**dynamic HC control technology**

Ergonomic rigid internal structure. It houses the heel into the right seat, adjusting the foot support and control of the ankle sideways movements. It keeps the foot tight to the shoe, allowing the perfect fit.



### Torsional stability

**STABIL•ACTIVE**

Support made of rigid plastic material. It stabilizes the heel bone, the instep and tarsal joints, without altering energy absorption. A support for the natural movement of the foot; it provides comfort and greater stability.




### Electrical features

**WED**

Wire Electricity Discharge

Strip with 4 filaments of carbon fiber, ensuring proven anti-static properties of the footwear over time.



### Other

**DUALMICRO DWTWICKO**

Double non-slip layer of microfibre, resistant up to 200,000 cycles. Makes the footwear more comfortable, blocking the foot during use.