



EN ISO 20345:2011

URBAN
CAPRI
82149-11L
S3 *CI SRC

Size: 36-48
Weight: 580 gr.

Fit: 11

Working Environment:
 Multipurpose, Wood-metal carpentry, Logistics and Light Industry, Components and Automotive

FEATURES

UPPER
 Drummed leather Hydro 1,8-2,0 mm

LINING
 3D Air circulation 320 gr.

ANTISLIP LINING
 DUALMICRO

INSOLE
 Climaction-Fit 337

TOE CAP
 Fiber cap SXT

RESISTANCE TO PERFORATION
 Textile resistant to 3.0 mm nail

TYPE
 Low Shoe

SOLE
PU DUAL-DENSITY SRC
 Two-component PU outsole with tread designed mainly for indoor use. Self-cleaning design and highly non-slip grip. SRC Antistip standard.



SRC (SRA+SRB)



SRA CERAMIC + DETERGENT SOLUTION	FLAT ≥0.32	0.47
	HEEL (CONTACT ANGLE °) ≥0.28	0.43
SRB STEEL + GLYCEROL	FLAT ≥0.18	0.21
	HEEL (CONTACT ANGLE °) ≥0.13	0.16

SOLE 82
 PU - PU
 EN ISO 20344:2011

TECHNOLOGIES

Removable Insole **337**
climaction fit

Removable anatomic and ergonomic insole. Absorbent and transpiring open-cell foam support. Keeps feet fresh. Specifically-designed thermoforming for exceptional comfort.



Protection elements
RESISTANT TO 3.0 mm NAILS **fibercap sxt**

Composite toe cap with fiberglass. Resistant to over 200J. Non metal perforation resistant insert to over 1100 N with a 3.0 mm truncated cone nail. Protection over the entire sole of the foot. Flexible and comfortable



Lateral stability
dynamic HC control technology

Ergonomic rigid internal structure. It houses the heel into the right seat, adjusting the foot support and control of the ankle sideways movements. It keeps the foot tight to the shoe, allowing the perfect fit.



Torsional stability
STABIL•ACTIVE

Support made of rigid plastic material. It stabilizes the heel bone, the instep and tarsal joints, without altering energy absorption. A support for the natural movement of the foot; it provides comfort and greater stability.



Electrical features
WED
 Wire Electricity Discharge

Strip with 4 filaments of carbon fiber, ensuring proven anti-static properties of the footwear over time.



Other
DUALMICRO DUALMICRO

Double non-slip layer of microfibre, resistant up to 200,000 cycles. Makes the footwear more comfortable, blocking the foot during use.