



EN ISO 20345:2011



URBAN
CAPRI
82149-16L

S3 *CI SRC

Size: 36-48
Weight: 580 gr.

Fit: 11

Working Environment:
Multipurpose, Wood-metal carpentry, Logistics and Light Industry, Components and Automotive



FEATURES

UPPER

Drummed leather Hydro 1,8-2,0 mm

LINING

3D Air circulation 320 gr.

ANTISLIP LINING
DUALMICRO

INSOLE

Climaction-Fit 337

TOE CAP

Fiber cap SXT

RESISTANCE TO PERFORATION

Textile resistant to 3.0 mm nail

TYPE

Low Shoe

SOLE

PU / PU ESD-PLUS SRC

Double density PU sole, Outer- and in-between sole with ESD compound. For use in contact with sensitive electronic equipment. Light and comfortable, very versatile, highly non-slip SRC Antislip standard.

TECHNOLOGIES


Removable Insole

337
climaction fit

Removable anatomic and ergonomic insole. Absorbent and transpiring open-cell foam support. Keeps feet fresh. Specifically-designed thermoforming for exceptional comfort.



Protection elements



Composite toecap with fiberglass. Resistant to over 200J. Non metal perforation resistant insert to over 1100 N with a 3.0 mm truncated cone nail. Protection over the entire sole of the foot. Flexible and comfortable



Lateral stability

dynamic HC control technology

Ergonomic rigid internal structure. It houses the heel into the right seat, adjusting the foot support and control of the ankle sideways movements. It keeps the foot tight to the shoe, allowing the perfect fit.



Torsional stability

STABIL•ACTIVE

Support made of rigid plastic material. It stabilizes the heel bone, the instep and tarsal joints, without altering energy absorption. A support for the natural movement of the foot; it provides comfort and greater stability.



Electrical features

WED

Wire Electricity Discharge

Strip with 4 filaments of carbon fiber, ensuring proven anti-static properties of the footwear over time.



Other

DUALMICRO DUALMICRO

Double non-slip layer of microfibre, resistant up to 200,000 cycles. Makes the footwear more comfortable, blocking the foot during use.



SRC (SRA+SRB)



SOLE 82
PU - PU

| | | |
|---|---|----------------------------|
| SRA CERAMIC + DETERGENT SOLUTION | FLAT ≥0.32 HEEL (CONTACT ANGLE °) ≥0.28 | 0.47 0.43 |
| SRB STEEL + GLYCEROL | FLAT ≥0.18 HEEL (CONTACT ANGLE °) ≥0.13 | 0.21 0.16 |

EN ISO 20344:2011