



EN ISO 20345:2011



URBAN

**CAPRI**
**83149-17L**
**S3 \*CI SRC**
**Size:** 49 and 50

**Weight:** 820 gr.

**Fit:** 11

**Working Environment:**

Multipurpose, Wood-metal carpentry, Logistics and Light Industry, Components and Automotive



## FEATURES

### UPPER

Drummed leather Hydro 1,8-2,0 mm

### LINING

3D Air circulation 320 gr.

### ANTISLIP LINING

DUALMICRO

### INSOLE

Climaction-Fit 337

### TOE CAP

Fiber cap SXT

### RESISTANCE TO PERFORATION

KX Antiperforation PS

### TYPE

Low Shoe

### SOLE

**PU / PU ESD-PLUS SRC**

Double density PU sole, Outer- and in-between sole with ESD compound. For use in contact with sensitive electronic equipment. Light and comfortable, very versatile, highly non-slip SRC Antislip standard.

## TECHNOLOGIES

### Removable Insole

**337 climaction fit**

Removable anatomic and ergonomic insole. Absorbent and transpiring open-cell foam support. Keeps feet fresh. Specifically-designed thermoforming for exceptional comfort.



### Protection elements



RESISTANT TO 3.0 mm. NAILS

**fibercap sxt**

Composite toecap with fiberglass. Resistant to over 200J. Non metal perforation resistant insert to over 1100 N with a 3.0 mm truncated cone nail. Protection over the entire sole of the foot. Flexible and comfortable



### Torsional stability


**STABIL ACTIVE**

Support made of rigid plastic material. It stabilizes the heel bone, the instep and tarsal joints, without altering energy absorption. A support for the natural movement of the foot; it provides comfort and greater stability.



### Electrical features



Wire Electricity Discharge

Strip with 4 filaments of carbon fiber, ensuring proven anti-static properties of the footwear over time.



## SRC (SRA+SRB)


 SOLE 83  
 PU - PU

<b>SRA</b> CERAMIC + DETERGENT SOLUTION	FLAT ≥0.32 HEEL (CONTACT ANGLE 7°) ≥0.28	<b>0.47</b>
<b>SRB</b> STEEL + GLYCEROL	FLAT ≥0.18 HEEL (CONTACT ANGLE 7°) ≥0.13	<b>0.21</b>
		<b>0.16</b>

EN ISO 20344:2011

### Other

**DUALMICRO**  
**DRYWICKBO**

Double non-slip layer of microfibre, resistant up to 200,000 cycles. Makes the footwear more comfortable, blocking the foot during use.